NSN 6210-01-116-1259

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-116-1259

Hazardous Locations/environmental Protection:

Cold resistant and dripproof and electromagnetic radiation suppressive and heat resistant and humidity resistant and vibration resistant and
explosion proof and shock resistant
Overall Length:
2.420 inches
Overall Height:
0.960 inches
Overall Width:
0.960 inches
Lamp Base Type Accommodated:
Submidget flanged
Lamp Bulb Size Designator:
T-1
Lens Quantity:
1
Lens Color:
Black single light 1st position horizontal
Multilamp Circuit Type:
Four lamp common
Lamp Industry Number:
6839
Lens Mounting Method:
Flange
Mounting Method:
Panel
Panel Thickness For Which Designed:
0.188 inches
Panel Accommodation Hole Width:
0.689 inches
Lamp Type Accommodated And Quantity:
4 incandescent
Lens Type:
Flat, rectangular single light 1st position horizontal
Panel Accommodation Hole Height:
0.689 inches
Lens Light Transmission Characteristic:
Transferent stands Bulkt Ast analytica beginning

Translucent single light 1st position horizontal

Transmitted Legend Color:

White single light 1st position horizontal full display division a

Lens Legend:

Pwr on; enable single light 1st position horizontal full display division a

Transmitted Light Color:

Black single light 1st position horizontal full display division a

NSN 6210-01-116-1259

Indicator Light - Page 2 of 2



Lens Back Surface Condition:
Smooth single light 1st position horizontal
Lens Face Surface Condition:
Smooth single light 1st position horizontal
Material:
Stainless steel body
Precious Material And Location:
Lamp contacts silver
Precious Material And Weight:
0.040 silver grains, troy
Precious Material:
Silver
Style Designator:
Rectangular frame type
Terminal Type And Quantity:
5 solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Yes - demil/mli

Fiig: A065a0