NSN 6210-01-116-1260

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-116-1260

Hazardous Locations/environmental Protection:

| Cold resistant and dripproof and electromagnetic radiation suppressive and heat resistant and humidity resistant and vibration resistant and |
|--|
| explosion proof and shock resistant |
| Overall Length: |
| 2.420 inches |
| Overall Height: |
| 0.960 inches |
| Overall Width: |
| 0.960 inches |
| Lamp Base Type Accommodated: |
| Submidget flanged |
| Lamp Bulb Size Designator: |
| T-1 |
| Lens Quantity: |
| 1 |
| Lens Color: |
| Black single light 1st position horizontal |
| Multilamp Circuit Type: |
| Four lamp common |
| Lamp Industry Number: |
| 6839 |
| Lens Mounting Method: |
| Flange |
| Mounting Method: |
| Panel |
| Panel Thickness For Which Designed: |
| 0.188 inches |
| Panel Accommodation Hole Width: |
| 0.689 inches |
| Lamp Type Accommodated And Quantity: |
| 4 incandescent |
| Lens Type: |
| Flat, rectangular single light 1st position horizontal |
| Panel Accommodation Hole Height: |
| 0.689 inches |
| Lens Light Transmission Characteristic: |
| Translucent single light 1st position horizontal |

Transmitted Legend Color:

Red single light 1st position horizontal full display division a

Lens Legend:

Over; ride single light 1st position horizontal full display division a

Transmitted Light Color:

Black single light 1st position horizontal full display division a

NSN 6210-01-116-1260

Indicator Light - Page 2 of 2



| Lens Back Surface Condition: |
|---|
| Smooth single light 1st position horizontal |
| Lens Face Surface Condition: |
| Smooth single light 1st position horizontal |
| Material: |
| Stainless steel body |
| Precious Material And Location: |
| Lamp contacts silver |
| Precious Material And Weight: |
| 0.040 silver grains, troy |
| Precious Material: |
| Silver |
| Style Designator: |
| Rectangular frame type |
| Terminal Type And Quantity: |
| 5 solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Yes - demil/mli

Fiig: A065a0