## NSN 6210-01-118-5022

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-118-5022

Overall Length:
2.249 inches
Overall Diameter:
Between 0.943 inches and 0.963 inches
Lamp Base Type Accommodated:
Miniature bayonet
Lamp Bulb Size Designator:
T-3 1/4
Lens Quantity:
1
Lens Color:
Amber single light 1st position horizontal
Panel Accommodation Hole Diameter:
0.688 inches
Lens Mounting Method:
Screw in
Mounting Method:
Panel
Panel Thickness For Which Designed:
0.312 inches
Lamp Type Accommodated And Quantity:
1 neon
Lens Type:
Lens Type:  Dome, knurled, internal thread single light 1st position horizontal
••
Dome, knurled, internal thread single light 1st position horizontal
Dome, knurled, internal thread single light 1st position horizontal  Lens Light Transmission Characteristic:
Dome, knurled, internal thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
Dome, knurled, internal thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:
Dome, knurled, internal thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Amber single light 1st position horizontal full display division a
Dome, knurled, internal thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Amber single light 1st position horizontal full display division a  Lens Back Surface Condition:
Dome, knurled, internal thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Amber single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal
Dome, knurled, internal thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Amber single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:
Dome, knurled, internal thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Amber single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal
Dome, knurled, internal thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Amber single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:
Dome, knurled, internal thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Amber single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Copper alloy body
Dome, knurled, internal thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Amber single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Copper alloy body  Surface Treatment:
Dome, knurled, internal thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Amber single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Copper alloy body  Surface Treatment:  Nickel body
Dome, knurled, internal thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Amber single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Copper alloy body  Surface Treatment:  Nickel body  Style Designator:
Dome, knurled, internal thread single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Amber single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Copper alloy body  Surface Treatment:  Nickel body  Style Designator:  Round frame, round lens type

2 quick disconnect, male

## NSN 6210-01-118-5022

Indicator Light - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A065a0