NSN 6210-01-121-9792

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-121-9792

Hazardous Locations/environmental Protection:
Electromagnetic radiation suppressive and vibration resistant and shock resistant
Overall Length:
2.060 inches
Overall Height:
Between 0.679 inches and 0.689 inches
Overall Width:
Between 0.679 inches and 0.689 inches
Filter Color:
Red single light 1st position horizontal full display division a
Lamp Base Type Accommodated:
Midget flanged
Lamp Bulb Size Designator: T-1 3/4
Lens Quantity:
Lens Color:
White single light 1st position horizontal
Filter Quantity:
1 Multileme Circuit Turcu
Multilamp Circuit Type:
Four lamp separate
Lamp Industry Number:
7333
End Application:
Ship, ohio class ssn (trident)
Lens Mounting Method:
Push in
Mounting Method:
Panel Thickness For Which Designed:
0.220 inches
Panel Accommodation Hole Width:
Between 0.689 inches and 0.699 inches
Lamp Type Accommodated And Quantity:
4 incandescent
Lens Type:
Flat, square shank single light 1st position horizontal
Panel Accommodation Hole Height:
Between 0.689 inches and 0.699 inches
Lens Light Transmission Characteristic:
Translucent single light 1st position horizontal

NSN 6210-01-121-9792

Indicator Light - Page 2 of 2



Transmitted Legend Color: Black single light 1st position horizontal full display division a Lens Legend: No go single light 1st position horizontal full display division a Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Stainless steel body **Precious Material And Location:** Lamp contacts gold **Precious Material And Weight:** 0.040 gold grains, troy **Precious Material:** Gold **Surface Treatment:** Passivate body Style Designator: Rectangular frame type **Terminal Type And Quantity:** 5 solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A065a0