## NSN 6210-01-123-0212

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-123-0212

Hazardous Locations/environmental Pro	tection:
---------------------------------------	----------

Explosion proof and shock resistant and humidity resistant and vibration resistant

**Overall Length:** 

2.375 inches

**Overall Height:** 

0.750 inches

**Overall Width:** 

1.000 inches

**Filter Color:** 

White single light 1st position horizontal full display division a

**Lamp Base Type Accommodated:** 

Midget flanged

Lamp Bulb Size Designator:

T-1 3/4

Lens Quantity:

**Lens Color:** 

Colorless single light 1st position horizontal

Filter Quantity:

**Multilamp Circuit Type:** 

Two lamp common

**Lens Mounting Method:** 

Flange

**Mounting Method:** 

Panel

Panel Thickness For Which Designed:

Between 0.031 inches and 0.250 inches

**Panel Accommodation Hole Width:** 

0.920 inches

**Lamp Type Accommodated And Quantity:** 

2 incandescent

Lens Type:

Display screen single light 1st position horizontal

**Panel Accommodation Hole Height:** 

0.670 inches

**Lens Light Transmission Characteristic:** 

Transparent single light 1st position horizontal

**Transmitted Legend Color:** 

Black single light 1st position horizontal full display division a

Lens Legend:

Slo; loaded single light 1st position horizontal full display division a

## NSN 6210-01-123-0212

Indicator Light - Page 2 of 2

Demilitarization:

No Fiig: A065a0



Transmitted Light Color:
White single light 1st position horizontal full display division a
Lens Back Surface Condition:
Smooth single light 1st position horizontal
Lens Face Surface Condition:
Smooth single light 1st position horizontal
Special Features:
Operates -54 degrees c to 71 degrees c, 0 to 70, 000 ft min altitude
Material:
Stainless steel body
Style Designator:
Rectangular frame type
Terminal Type And Quantity:
3 screw and 3 solder lug
Shelf Life:
N/a
Unit Of Measure: