

View Online at <https://aerobasegroup.com/nsn/6210-01-128-5231>

**Hazardous Locations/environmental Protection:**

Humidity resistant and vibration resistant and explosion proof and shock resistant

**Overall Length:**

2.375 inches

**Overall Height:**

0.750 inches

**Overall Width:**

1.000 inches

**Filter Color:**

White single light 1st position horizontal full display division a

**Lamp Base Type Accommodated:**

Midget flanged

**Lamp Bulb Size Designator:**

T-1 3/4

**Lens Quantity:**

1

**Lens Color:**

Colorless single light 1st position horizontal

**Filter Quantity:**

1

**Multilamp Circuit Type:**

Two lamp common

**Lens Mounting Method:**

Flange

**Mounting Method:**

Panel

**Panel Thickness For Which Designed:**

Between 0.031 inches and 0.250 inches

**Panel Accommodation Hole Width:**

0.920 inches

**Lamp Type Accommodated And Quantity:**

2 incandescent

**Lens Type:**

Display screen single light 1st position horizontal

**Panel Accommodation Hole Height:**

0.670 inches

**Lens Light Transmission Characteristic:**

Transparent single light 1st position horizontal

**Transmitted Legend Color:**

Black single light 1st position horizontal full display division a

**Lens Legend:**

Sorter; loaded single light 1st position horizontal full display division a

**Transmitted Light Color:**

White single light 1st position horizontal full display division a

**Lens Back Surface Condition:**

Smooth single light 1st position horizontal

**Lens Face Surface Condition:**

Smooth single light 1st position horizontal

**Extra Long Reference Number:**

80ea1c2f (w) j111n13 sorter, loaded

**Special Features:**

Operates -54 degrees c to 71 degrees c, 0 to 70, 000 ft min altitude

**Material:**

Stainless steel body

**Style Designator:**

Rectangular frame type

**Terminal Type And Quantity:**

3 screw and 3 solder lug

**Reference Number Differentiating Characteristics:**

As differentiated by extra long reference number

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A065a0