NSN 6210-01-128-6280

Hazardous Locations/environmental Protection:

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-128-6280

| Dusttight and oiltight and watertight | | | | |
|--|--|--|--|--|
| Overall Length: | | | | |
| 3.438 inches | | | | |
| Overall Diameter: | | | | |
| 1.141 inches | | | | |
| Lamp Base Type Accommodated: | | | | |
| Candelabra screw | | | | |
| Lamp Bulb Size Designator: | | | | |
| S-6 | | | | |
| Lens Quantity: | | | | |
| 1 | | | | |
| Lens Color: | | | | |
| Red single light 1st position horizontal | | | | |
| Panel Accommodation Hole Diameter: | | | | |
| 1.000 inches | | | | |
| Lens Mounting Method: | | | | |
| Screw on | | | | |
| Mounting Method: | | | | |
| Panel | | | | |
| Panel Thickness For Which Designed: | | | | |
| 0.562 inches | | | | |
| Features Provided: | | | | |
| Blackout degree, complete and dimming device | | | | |
| Lamp Type Accommodated And Quantity: | | | | |
| 1 incandescent | | | | |
| Lens Type: | | | | |
| Convex, knurled single light 1st position horizontal | | | | |
| Lens Light Transmission Characteristic: | | | | |
| Translucent single light 1st position horizontal | | | | |
| Transmitted Light Color: | | | | |
| Red single light 1st position horizontal full display division a | | | | |
| Lens Back Surface Condition: | | | | |
| Frosted single light 1st position horizontal | | | | |
| Lens Face Surface Condition: | | | | |
| Smooth single light 1st position horizontal | | | | |
| Material: | | | | |
| Copper alloy body | | | | |
| Surface Treatment: | | | | |
| Nickel body | | | | |
| Style Designator: | | | | |

Round frame, round lens type

NSN 6210-01-128-6280

Indicator Light - Page 2 of 2



| Furr | nished | Items | And | Quantity: |
|------|--------|-------|-----|-----------|
| | | | | |

1 hexagon nut and 1 lock washer

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0