

View Online at <https://aerobasegroup.com/nsn/6210-01-139-4843>

**Hazardous Locations/environmental Protection:**

Dust resistant and salt spray resistant and vibration resistant and shock resistant

**Overall Length:**

0.630 inches

**Overall Height:**

0.805 inches

**Overall Width:**

4.188 inches

**Filter Color:**

Green, aviation, mil-c-25050 type 1 single light 1st position horizontal full display division a and yellow, aviation, mil-c-25050 type 1 single light 1st position horizontal full display division a

**Lens Quantity:**

1

**Lens Color:**

White, aviation, mil-c-25050 type 1 single light 1st position horizontal

**Filter Quantity:**

20

**Multilamp Circuit Type:**

Two lamp common

**Lens Mounting Method:**

Flange

**Mounting Method:**

Panel

**Panel Thickness For Which Designed:**

0.062 inches

**Panel Accommodation Hole Width:**

3.727 inches

**Lens Type:**

Flat, rectangular single light 1st position horizontal

**Panel Accommodation Hole Height:**

0.742 inches

**Lens Light Transmission Characteristic:**

Translucent single light 1st position horizontal

**Transmitted Legend Color:**

Green, aviation, mil-c-25050 type 1 single light 1st position horizontal full display division a and yellow, aviation, mil-c-25050 type 1 single light 1st position horizontal full display division a

**Lens Legend:**

Frame mount pan ecs ir ls; frame sc pan ir nr ir ls single light 1st position horizontal full display division a

**Transmitted Light Color:**

Black single light 1st position horizontal full display division a

**Lens Back Surface Condition:**

Smooth single light 1st position horizontal

**Lens Face Surface Condition:**

Painted single light 1st position horizontal

**Special Features:**

Lamp accommodation quantity: 20

**Style Designator:**

Rectangular frame type

**Terminal Type And Quantity:**

20 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A065a0