Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-139-6535

| Hazardous Locations/environmental Protection:                            |
|--|
| Vibration resistant and shock resistant                                  |
| Overall Length:  |
| 2.070 inches   |
| Overall Height:  |
| 0.960 inches   |
| Overall Width:   |
| 1.200 inches   |
| Filter Color:  |
| Red single light 1st position horizontal 4way split display division d   |
| Lamp Base Type Accommodated:   |
| Midget flanged   |
| Lamp Bulb Size Designator:   |
| T-1 3/4  |
| Lens Quantity:   |
| 1  |
| Lens Color:  |
| White single light 1st position horizontal                               |
| Filter Quantity:   |
| 4  |
| Multilamp Circuit Type:  |
| Four lamp common   |
| Lens Mounting Method:  |
| Push in  |
| Mounting Method:   |
| Panel  |
| Panel Thickness For Which Designed:                                      |
| Between 0.050 inches and 0.250 inches                                    |
| Panel Accommodation Hole Width:  |
| 1.115 inches   |
| Lamp Type Accommodated And Quantity:                                     |
| 4 incandescent   |
| Lens Type:   |
| Flat, narrow single light 1st position horizontal                        |
| Panel Accommodation Hole Height:   |
| 0.875 inches   |
| Lens Light Transmission Characteristic:                                  |
| Translucent single light 1st position horizontal                         |
| Transmitted Light Color:   |
| Green single light 1st position horizontal 4way split display division b |
| Lens Back Surface Condition:   |
| Smooth single light 1st position horizontal                              |

## NSN 6210-01-139-6535

Indicator Light - Page 2 of 2



Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features: Narrow front lens plate Style Designator: Rectangular frame type Terminal Type And Quantity: 5 solder lug Shelf Life: N/a Unit Of Measure:

Demilitarization:

No

Fiig:

A065a0