NSN 6210-01-140-1520

Indicator Light - Page 1 of 2

Furnished Items And Quantity: 1 hexagon nut and 1 lock washer



View Online at https://aerobasegroup.com/nsn/6210-01-140-1520

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
3.660 inches
Overall Diameter:
1.670 inches
Lamp Base Type Accommodated:
Midget flanged
Lamp Bulb Size Designator:
T-1 3/4
Lens Quantity:
1
Lens Color:
Green single light 1st position horizontal
Panel Accommodation Hole Diameter:
0.688 inches
End Application:
Skidd class ddg; aircraft, thunderbolt ii, a-10; virginia class cgn (41); sonar rubber domes (srds); fms - knox class ff; spruance class dd
(963); arleigh burke class ddg; ticonderoga class cg (47); marine hardware & hull doors
Lens Mounting Method:
Screw in
Mounting Method:
Panel
Panel Thickness For Which Designed:
0.218 inches
Lamp Type Accommodated And Quantity:
1 incandescent
Lens Type:
Convex, knurled, threaded shank single light 1st position horizontal
Lens Light Transmission Characteristic:
Translucent single light 1st position horizontal
Transmitted Light Color:
Green single light 1st position horizontal full display division a
Lens Back Surface Condition:
Smooth single light 1st position horizontal
Lens Face Surface Condition:
Smooth single light 1st position horizontal
Material:
Copper alloy body
Style Designator:
Round frame, round lens type

NSN 6210-01-140-1520

Indicator Light - Page 2 of 2



Teri	m	ina	ıl .	Type	And	Quantity:

3 solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0