NSN 6210-01-141-1441

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-141-1441

| Hazardous Locations/environmental Protection: | | | | | | |
|---|--|--|--|--|--|--|
| Watertight and shock proof | | | | | | |
| Overall Length: | | | | | | |
| 2.430 inches | | | | | | |
| Overall Height: | | | | | | |
| 1.750 inches | | | | | | |
| Overall Width: | | | | | | |
| 2.125 inches | | | | | | |
| Lamp Base Type Accommodated: | | | | | | |
| Midget screw | | | | | | |
| Lamp Bulb Size Designator: | | | | | | |
| T-1 3/4 | | | | | | |
| Lens Quantity: | | | | | | |
| 1 | | | | | | |
| Lens Color: | | | | | | |
| Red single light 1st position horizontal | | | | | | |
| Multilamp Circuit Type: | | | | | | |
| Two lamp common | | | | | | |
| Lamp Industry Number: | | | | | | |
| 1769 | | | | | | |
| Lens Mounting Method: | | | | | | |
| Lens Mounting Method. | | | | | | |
| Screw on | | | | | | |
| | | | | | | |
| Screw on | | | | | | |
| Screw on Mounting Method: | | | | | | |
| Screw on Mounting Method: Unthreaded hole | | | | | | |
| Screw on Mounting Method: Unthreaded hole Features Provided: | | | | | | |
| Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer | | | | | | |
| Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: | | | | | | |
| Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent | | | | | | |
| Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: | | | | | | |
| Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal | | | | | | |
| Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal Lens Light Transmission Characteristic: | | | | | | |
| Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal | | | | | | |
| Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: | | | | | | |
| Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a | | | | | | |
| Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: | | | | | | |
| Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal | | | | | | |
| Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: | | | | | | |
| Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal | | | | | | |

_ . . .

Rectangular frame type

NSN 6210-01-141-1441

Indicator Light - Page 2 of 2



| F | urnished | Items | And | Quantity | 1 |
|---|----------|--------------|-----|----------|---|
| | | | | | |

10 flat washer and 1 gasket and 8 screw

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0