NSN 6210-01-147-6534

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-147-6534

Hazardous Locations/environmental Protection:

Electromagnetic radiation suppressive and vibration resistant and shock resistant

Overall Length:

2.060 inches

Overall Height:

Between 0.679 inches and 0.689 inches

Overall Width:

Between 0.679 inches and 0.689 inches

Filter Color:

Yellow single light 1st position horizontal full display division a

Lamp Base Type Accommodated:

Midget flanged

Lamp Bulb Size Designator:

T-1 3/4

Lens Quantity:

Lens Color:

Colorless single light 1st position horizontal

Filter Quantity:

1

Multilamp Circuit Type:

Two lamp common

End Application:

Ship, ohio class ssn (trident)

Lens Mounting Method:

Push in

Mounting Method:

Panel

Panel Thickness For Which Designed:

Between 0.031 inches and 0.300 inches

Panel Accommodation Hole Width:

Between 0.689 inches and 0.699 inches

Lamp Type Accommodated And Quantity:

2 incandescent

Lens Type:

Flat, square shank single light 1st position horizontal

Panel Accommodation Hole Height:

Between 0.690 inches and 0.705 inches

Lens Light Transmission Characteristic:

Transparent single light 1st position horizontal

Transmitted Legend Color:

Yellow single light 1st position horizontal full display division a

NSN 6210-01-147-6534

Indicator Light - Page 2 of 2



| Lens Legend: |
|--|
| Warning single light 1st position horizontal full display division a |
| Transmitted Light Color: |
| Black single light 1st position horizontal full display division a |
| Lens Back Surface Condition: |
| Smooth single light 1st position horizontal |
| Lens Face Surface Condition: |
| Painted single light 1st position horizontal |
| Material: |
| Stainless steel body |
| Surface Treatment: |
| Passivate body |
| Style Designator: |
| Rectangular frame type |
| Terminal Type And Quantity: |
| 5 solder stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A065a0