NSN 6210-01-148-8795

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-148-8795

| Hazardous Locations/environmental Protection: |
|--|
| Electromagnetic radiation suppressive and waterproof |
| Overall Length: |
| 1.460 inches |
| Overall Height: |
| 0.656 inches |
| Overall Width: |
| 1.875 inches |
| Filter Color: |
| Red single light 1st position horizontal horizontal split display division b |
| Lamp Base Type Accommodated: |
| Midget flanged |
| Lamp Bulb Size Designator: |
| T-1 3/4 |
| Lens Quantity: |
| 1 |
| Lens Color: |
| White single light 1st position horizontal |
| Filter Quantity: |
| 2 |
| Lens Mounting Method: |
| Push in |
| Mounting Method: |
| Panel |
| Panel Thickness For Which Designed: |
| 0.187 inches |
| Lamp Type Accommodated And Quantity: |
| 2 incandescent |
| Lens Type: |
| Flat, square shank single light 1st position horizontal |
| Lens Light Transmission Characteristic: |
| Translucent single light 1st position horizontal |
| Transmitted Legend Color: |
| Black single light 1st position horizontal horizontal split display division b |
| Lens Legend: |
| Go single light 1st position horizontal horizontal split display division a |
| Transmitted Light Color: |
| Green single light 1st position horizontal horizontal split display division a |
| Lens Back Surface Condition: |
| Smooth single light 1st position horizontal |
| Lens Face Surface Condition: |
| Smooth single light 1st position horizontal |
| |

NSN 6210-01-148-8795

Indicator Light - Page 2 of 2



Material:

Plastic phenolic body or plastic polycarbonate body or plastic polyamide body

Surface Treatment:

Anodize illumination directing device and chromium illumination directing device

Style Designator:

Rectangular frame type

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A065a0