NSN 6210-01-150-8215

Indicator Light Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-150-8215

Hazardous Locations/environmental Protection:				
Shock proof and watertight				
Overall Height:				
3.840 inches				
Overall Width:				
3.760 inches				
Lamp Base Type Accommodated:				
Midget screw				
Lamp Bulb Size Designator:				
T-1 3/4				
Lens Quantity:				
4				
Lens Color:				
Red single row 3rd position vertical				
Lamp Industry Number:				
1769				
Mounting Method:				
Bolt				
Features Provided:				
Transformer				
Lamp Type Accommodated And Quantity:				
8 incandescent				
Lens Type:				
Flat, round single row 4th position vertical				
Lens Light Transmission Characteristic:				
Translucent single row 3rd position vertical				
Transmitted Legend Color:				
White single row 4th position vertical full display division a				
Lens Legend:				
Lens Legend: Pump; no 2; failure single row 3rd position vertical full display division a				
Pump; no 2; failure single row 3rd position vertical full display division a				
Pump; no 2; failure single row 3rd position vertical full display division a Transmitted Light Color:				
Pump; no 2; failure single row 3rd position vertical full display division a Transmitted Light Color: Red single row 3rd position vertical full display division a				
Pump; no 2; failure single row 3rd position vertical full display division a Transmitted Light Color: Red single row 3rd position vertical full display division a Lens Back Surface Condition:				
Pump; no 2; failure single row 3rd position vertical full display division a Transmitted Light Color: Red single row 3rd position vertical full display division a Lens Back Surface Condition: Smooth single row 4th position vertical				
Pump; no 2; failure single row 3rd position vertical full display division a Transmitted Light Color: Red single row 3rd position vertical full display division a Lens Back Surface Condition: Smooth single row 4th position vertical Lens Face Surface Condition:				
Pump; no 2; failure single row 3rd position vertical full display division a Transmitted Light Color: Red single row 3rd position vertical full display division a Lens Back Surface Condition: Smooth single row 4th position vertical Lens Face Surface Condition: Smooth single row 4th position vertical				
Pump; no 2; failure single row 3rd position vertical full display division a Transmitted Light Color: Red single row 3rd position vertical full display division a Lens Back Surface Condition: Smooth single row 4th position vertical Lens Face Surface Condition: Smooth single row 4th position vertical Special Features:				
Pump; no 2; failure single row 3rd position vertical full display division a Transmitted Light Color: Red single row 3rd position vertical full display division a Lens Back Surface Condition: Smooth single row 4th position vertical Lens Face Surface Condition: Smooth single row 4th position vertical Special Features: 450 volts 60 cycles				
Pump; no 2; failure single row 3rd position vertical full display division a Transmitted Light Color: Red single row 3rd position vertical full display division a Lens Back Surface Condition: Smooth single row 4th position vertical Lens Face Surface Condition: Smooth single row 4th position vertical Special Features:				

Single strip type

NSN 6210-01-150-8215

Indicator Light Assembly - Page 2 of 2



Terminal	Type	And	Quantity:
-----------------	------	-----	-----------

8 solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0