

	NSN 6210-01-154-8306 Indicator Light - Page 1 of 2	A
\	View Online at https://aerobasegroup.com/nsn/6210-01-154-8306	
F	Hazardous Locations/environmental Protection:	
\	Vibration resistant and shock resistant	
C	Overall Length:	
1	1.750 inches	
C	Overall Height:	
Е	Between 0.950 inches and 0.970 inches	
C	Overall Width:	
Е	Between 1.190 inches and 2.210 inches	
F	Filter Color:	
F	Red single light 1st position horizontal horizontal split display division b	
L	Lamp Base Type Accommodated:	
N	Midget flanged	
L	Lamp Bulb Size Designator:	
Т	Г-1 3/4	
L	Lens Quantity:	
1	1	
L	Lens Color:	
C	Colorless single light 1st position horizontal	
F	Filter Quantity:	
4	4	
N	Multilamp Circuit Type:	
F	Four lamp separate	
L	Lamp Industry Number:	
3	327	
L	Lens Mounting Method:	
F	Flange	
N	Mounting Method:	
_	Panal	

Panel

Panel Thickness For Which Designed:

Between 0.020 inches and 0.250 inches

Panel Accommodation Hole Width:

1.110 inches

Lamp Type Accommodated And Quantity:

4 incandescent

Lens Type:

Display screen single light 1st position horizontal

Panel Accommodation Hole Height:

0.870 inches

Lens Light Transmission Characteristic:

Transparent single light 1st position horizontal

Transmitted Legend Color:

Black single light 1st position horizontal horizontal split display division b

NSN 6210-01-154-8306

Indicator Light - Page 2 of 2



-	_		_	
Lens	1 ^	~~	nd	
LCII3	ᆫ	ue	HU	١.

Differential; 3, 4 single light 1st position horizontal horizontal split display division b

Transmitted Light Color:

Red single light 1st position horizontal horizontal split display division b

Lens Back Surface Condition:

Smooth single light 1st position horizontal

Lens Face Surface Condition:

Smooth single light 1st position horizontal

Material:

Steel comp 304 body

Style Designator:

Rectangular frame type

Terminal Type And Quantity:

8 solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A065a0