NSN 6210-01-167-2730

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-167-2730

azardous Locations/environmental Protection:
ibration resistant and shock resistant
overall Length:
.750 inches
overall Height:
etween 0.950 inches and 0.970 inches
overall Width:
etween 1.190 inches and 2.210 inches
ilter Color:
ed single light 1st position horizontal horizontal split display divisio
amp Base Type Accommodated:
lidget flanged
amp Bulb Size Designator:
-1 3/4
ens Quantity:
ens Color:
colorless single light 1st position horizontal
ilter Quantity:
lultilamp Circuit Type:
our lamp separate
amp Industry Number:
27
ens Mounting Method:
lange
lounting Method:
anel
anel Thickness For Which Designed:
etween 0.020 inches and 0.250 inches
anel Accommodation Hole Width:
.110 inches
amp Type Accommodated And Quantity:
incandescent
ens Type:
splay screen single light 1st position horizontal
anel Accommodation Hole Height:
.870 inches

....

Lens Light Transmission Characteristic:

Transparent single light 1st position horizontal

Transmitted Legend Color:

Black single light 1st position horizontal horizontal split display division b

NSN 6210-01-167-2730

Indicator Light - Page 2 of 2



-	_		_	
Lens	1 ^	~~	nd	
LCII3	ᆫ	ue	HU	١.

Oxy tank; low single light 1st position horizontal horizontal split display division a

Transmitted Light Color:

Red single light 1st position horizontal horizontal split display division b

Lens Back Surface Condition:

Smooth single light 1st position horizontal

Lens Face Surface Condition:

Smooth single light 1st position horizontal

Material:

Stainless steel body

Surface Treatment:

Passivate body

Style Designator:

Rectangular frame type

Terminal Type And Quantity:

8 solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0