NSN 6210-01-173-2946

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-173-2946

			4 . 1 . 5
Hazardous I	l ocations/	environmen	tal Protection:

Electromagnetic radiation suppressive and humidity resistant and vibration resistant and shock resistant **Overall Length:** 1.970 inches **Overall Height:** 0.750 inches **Overall Width:** 0.750 inches **Filter Color:** White single light 1st position horizontal horizontal split display division a **Lamp Base Type Accommodated:** Midget flanged Lamp Bulb Size Designator: T-1 3/4 Lens Quantity: **Lens Color:** White single light 1st position horizontal Filter Quantity:

Multilamp Circuit Type:

Horizontal split

Lamp Industry Number:

7333

Lens Mounting Method:

Push in

Mounting Method:

Panel

Panel Thickness For Which Designed:

Between 0.031 inches and 0.300 inches

Panel Accommodation Hole Width:

Between 0.689 inches and 0.699 inches

Lamp Type Accommodated And Quantity:

4 incandescent

Lens Type:

Flat, square shank single light 1st position horizontal

Panel Accommodation Hole Height:

Between 0.689 inches and 0.699 inches

Lens Light Transmission Characteristic:

Translucent single light 1st position horizontal

Transmitted Legend Color:

White single light 1st position horizontal horizontal split display division b

NSN 6210-01-173-2946

Indicator Light - Page 2 of 2



-	_		_	
Lens	1 ^	~~	nd	
LCII3	ᆫ	ue	HU	١.

Wb single light 1st position horizontal horizontal split display division b

Transmitted Light Color:

Black single light 1st position horizontal horizontal split display division b

Lens Back Surface Condition:

Smooth single light 1st position horizontal

Lens Face Surface Condition:

Painted single light 1st position horizontal

Special Features:

Standard bezel

Material:

Stainless steel body

Style Designator:

Rectangular frame type

Terminal Type And Quantity:

6 solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A065a0