NSN 6210-01-179-0180

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-179-0180

d radio frequency

Hazardous Locations/environment	al Protection:
Dustproof and explosion proof nec cl.	I, gp.Abcd; cl.li, gp.Efg; cl.lii and fungus resistant and humidity resistant and
interference and salt spray resistant a	and shock resistant and vibration resistant and sand proof
Overall Length:	
2.190 inches	
Overall Height:	
0.781 inches	
Overall Width:	
0.781 inches	
Lamp Base Type Accommodated:	
Midget flanged	
Lamp Bulb Size Designator:	
T-1 3/4	
Multilamp Circuit Type:	
Horizontal split	
Mounting Method:	
Panel	
Panel Thickness For Which Design	ed:
Between 0.060 inches and 0.250 inch	nes
Panel Accommodation Hole Width:	
Between 0.734 inches and 0.750 inch	nes
Lamp Type Accommodated And Qu	uantity:
4 incandescent	
Panel Accommodation Hole Height	:
Between 0.734 inches and 0.750 inch	nes
Special Features:	
Thermal shock proof and acceleration	proof
Material:	
Aluminum body	
Precious Material And Location:	
Terminals gold	
Precious Material And Weight:	
0.040 gold grains, troy	
Precious Material:	
Gold	
Surface Treatment:	

Anodize body

Style Designator:

Rectangular frame type

Furnished Items And Quantity:

1 lock washer and 1 screw

Terminal Type And Quantity:

6 solder lug

NSN 6210-01-179-0180

Indicator Light - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0