## NSN 6210-01-182-4803

Indicator Light - Page 1 of 2



view Online at https://aerobasegroup.com/hsn/6210-01-162-4603
Hazardous Locations/environmental Protection:
Electromagnetic radiation suppressive
Overall Length:
2.260 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Filter Color:
Red single light 1st position horizontal full display division a
Lamp Base Type Accommodated:
Submidget flanged
Lamp Bulb Size Designator:
T-1
Lens Quantity:
1
Lens Color:
White single light 1st position horizontal
Filter Quantity:
1
Multilamp Circuit Type:
Four lamp common
Four lamp common  Lens Mounting Method:
Lens Mounting Method:
Lens Mounting Method: Push in
Lens Mounting Method: Push in Mounting Method:
Lens Mounting Method: Push in Mounting Method: Sleeve
Lens Mounting Method: Push in Mounting Method: Sleeve Lamp Type Accommodated And Quantity:
Lens Mounting Method: Push in Mounting Method: Sleeve Lamp Type Accommodated And Quantity: 4 incandescent
Lens Mounting Method: Push in Mounting Method: Sleeve Lamp Type Accommodated And Quantity: 4 incandescent Lens Type:
Lens Mounting Method: Push in Mounting Method: Sleeve Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, square shank single light 1st position horizontal
Lens Mounting Method: Push in Mounting Method: Sleeve Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic:
Lens Mounting Method: Push in Mounting Method: Sleeve Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal
Lens Mounting Method: Push in Mounting Method: Sleeve Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color:
Lens Mounting Method: Push in Mounting Method: Sleeve Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: Black single light 1st position horizontal full display division a
Lens Mounting Method: Push in Mounting Method: Sleeve Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: Black single light 1st position horizontal full display division a Lens Legend:
Lens Mounting Method: Push in Mounting Method: Sleeve Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: Black single light 1st position horizontal full display division a Lens Legend: 3 stc-a; auto; shutdown single light 1st position horizontal full display division a
Lens Mounting Method: Push in Mounting Method: Sleeve Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: Black single light 1st position horizontal full display division a Lens Legend: 3 stc-a; auto; shutdown single light 1st position horizontal full display division a Transmitted Light Color:
Lens Mounting Method: Push in Mounting Method: Sleeve Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, square shank single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: Black single light 1st position horizontal full display division a Lens Legend: 3 stc-a; auto; shutdown single light 1st position horizontal full display division a Transmitted Light Color: Red single light 1st position horizontal full display division a

Smooth single light 1st position horizontal

## NSN 6210-01-182-4803

Indicator Light - Page 2 of 2



Material:
Stainless steel body
Surface Treatment:
Passivate body
Style Designator:
Rectangular frame type
Furnished Items And Quantity:
1 mounting sleeve
Terminal Type And Quantity:
5 solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A065a0