Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-204-1096

| Hazardous Locations/environmental Protection: |
|--|
| Shock resistant and vibration resistant |
| Overall Length: |
| 2.040 inches |
| Overall Height: |
| 0.960 inches |
| Overall Width: |
| 1.200 inches |
| Filter Color: |
| White single light 1st position horizontal horizontal split display division a |
| Lamp Base Type Accommodated: |
| Midget flanged |
| Lamp Bulb Size Designator: |
| T-1 3/4 |
| Lens Quantity: |
| 1 |
| Lens Color: |
| Colorless single light 1st position horizontal |
| Filter Quantity: |
| 4 |
| Multilamp Circuit Type: |
| Horizontal split |
| Lens Mounting Method: |
| Flange |
| Mounting Method: |
| Panel |
| Panel Thickness For Which Designed: |
| Between 0.050 inches and 0.250 inches |
| Panel Accommodation Hole Width: |
| 1.115 inches |
| Lamp Type Accommodated And Quantity: |
| 4 incandescent |
| Lens Type: |
| Display screen single light 1st position horizontal |
| Panel Accommodation Hole Height: |
| 0.875 inches |
| Lens Light Transmission Characteristic: |
| Transparent single light 1st position horizontal |
| Transmitted Light Color: |
| White single light 1st position horizontal horizontal split display division a |
| Lens Back Surface Condition: |
| Smooth single light 1st position horizontal |
| |

NSN 6210-01-204-1096

Indicator Light - Page 2 of 2



Lens Face Surface Condition:

Smooth single light 1st position horizontal

Material:

Stainless steel body

Surface Treatment:

Passivate body

Style Designator:

Rectangular frame type

Terminal Type And Quantity:

5 solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A065a0