## NSN 6210-01-212-9587

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-212-9587

Hazardous Locations/environmental Protection:  Watertight  Overall Length: 2.344 inches  Overall Diameter: 0.828 inches  Lamp Base Type Accommodated:  Miniature bayonet  Lamp Bulb Size Designator: T-3 1/4  Lens Quantity: 1  Lens Color: Red single light 1st position horizontal  Panel Accommodation Hole Diameter: 0.688 inches  Lens Mounting Method: Screw in  Mounting Method: Panel Panel Thickness For Which Designed: 0.062 inches  Features Provided: Blackout degree, partial  Lamp Type Accommodated And Quantity: 1 incandescent  Lens Type: Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color:
Overall Length:  2.344 inches  Overall Diameter:  0.828 inches  Lamp Base Type Accommodated:  Miniature bayonet  Lamp Bulb Size Designator:  T-3 1/4  Lens Quantity:  1  Lens Color:  Red single light 1st position horizontal  Panel Accommodation Hole Diameter:  0.688 inches  Lens Mounting Method:  Screw in  Mounting Method:  Panel  Panel Thickness For Which Designed:  0.062 inches  Features Provided:  Blackout degree, partial  Lamp Type Accommodated And Quantity:  1 incandescent  Lens Type:  Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
2.344 inches  Overall Diameter: 0.828 inches  Lamp Base Type Accommodated: Miniature bayonet  Lamp Bulb Size Designator: T-3 1/4  Lens Quantity: 1  Lens Color: Red single light 1st position horizontal  Panel Accommodation Hole Diameter: 0.688 inches  Lens Mounting Method: Screw in  Mounting Method: Panel Panel Thickness For Which Designed: 0.062 inches  Features Provided: Blackout degree, partial  Lamp Type Accommodated And Quantity: 1 incandescent  Lens Type: Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Overall Diameter:  0.828 inches  Lamp Base Type Accommodated:  Miniature bayonet  Lamp Bulb Size Designator:  T-3 1/4  Lens Quantity:  1  Lens Color:  Red single light 1st position horizontal  Panel Accommodation Hole Diameter:  0.688 inches  Lens Mounting Method:  Screw in  Mounting Method:  Panel  Panel Thickness For Which Designed:  0.062 inches  Features Provided:  Blackout degree, partial  Lamp Type Accommodated And Quantity:  1 incandescent  Lens Type:  Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
0.828 inches  Lamp Base Type Accommodated:  Miniature bayonet  Lamp Bulb Size Designator:  T-3 1/4  Lens Quantity:  1  Lens Color:  Red single light 1st position horizontal  Panel Accommodation Hole Diameter:  0.688 inches  Lens Mounting Method:  Screw in  Mounting Method:  Panel  Panel Thickness For Which Designed:  0.062 inches  Features Provided:  Blackout degree, partial  Lamp Type Accommodated And Quantity:  1 incandescent  Lens Type:  Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
Lamp Base Type Accommodated:  Miniature bayonet  Lamp Bulb Size Designator:  T-3 1/4  Lens Quantity:  1  Lens Color:  Red single light 1st position horizontal  Panel Accommodation Hole Diameter:  0.688 inches  Lens Mounting Method:  Screw in  Mounting Method:  Panel  Panel Thickness For Which Designed:  0.062 inches  Features Provided:  Blackout degree, partial  Lamp Type Accommodated And Quantity:  1 incandescent  Lens Type:  Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
Miniature bayonet  Lamp Bulb Size Designator: T-3 1/4  Lens Quantity: 1  Lens Color: Red single light 1st position horizontal  Panel Accommodation Hole Diameter: 0.688 inches  Lens Mounting Method: Screw in  Mounting Method: Panel  Panel Thickness For Which Designed: 0.062 inches  Features Provided: Blackout degree, partial  Lamp Type Accommodated And Quantity: 1 incandescent  Lens Type: Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Lamp Bulb Size Designator: T-3 1/4 Lens Quantity: 1 Lens Color: Red single light 1st position horizontal Panel Accommodation Hole Diameter: 0.688 inches Lens Mounting Method: Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.062 inches Features Provided: Blackout degree, partial Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
T-3 1/4  Lens Quantity:  1  Lens Color:  Red single light 1st position horizontal  Panel Accommodation Hole Diameter:  0.688 inches  Lens Mounting Method:  Screw in  Mounting Method:  Panel  Panel Thickness For Which Designed:  0.062 inches  Features Provided:  Blackout degree, partial  Lamp Type Accommodated And Quantity:  1 incandescent  Lens Type:  Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
Lens Quantity:  1 Lens Color: Red single light 1st position horizontal Panel Accommodation Hole Diameter: 0.688 inches Lens Mounting Method: Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.062 inches Features Provided: Blackout degree, partial Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Lens Color: Red single light 1st position horizontal Panel Accommodation Hole Diameter: 0.688 inches Lens Mounting Method: Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.062 inches Features Provided: Blackout degree, partial Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Lens Color:  Red single light 1st position horizontal  Panel Accommodation Hole Diameter:  0.688 inches  Lens Mounting Method:  Screw in  Mounting Method:  Panel  Panel Thickness For Which Designed:  0.062 inches  Features Provided:  Blackout degree, partial  Lamp Type Accommodated And Quantity:  1 incandescent  Lens Type:  Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
Red single light 1st position horizontal  Panel Accommodation Hole Diameter:  0.688 inches  Lens Mounting Method:  Screw in  Mounting Method:  Panel  Panel Thickness For Which Designed:  0.062 inches  Features Provided:  Blackout degree, partial  Lamp Type Accommodated And Quantity:  1 incandescent  Lens Type:  Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
Panel Accommodation Hole Diameter:  0.688 inches  Lens Mounting Method: Screw in  Mounting Method: Panel Panel Thickness For Which Designed: 0.062 inches  Features Provided: Blackout degree, partial  Lamp Type Accommodated And Quantity: 1 incandescent  Lens Type: Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Cens Mounting Method: Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.062 inches Features Provided: Blackout degree, partial Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Lens Mounting Method: Screw in Mounting Method: Panel Panel Thickness For Which Designed: 0.062 inches Features Provided: Blackout degree, partial Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Screw in  Mounting Method: Panel Panel Thickness For Which Designed: 0.062 inches Features Provided: Blackout degree, partial Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Mounting Method: Panel Panel Thickness For Which Designed: 0.062 inches Features Provided: Blackout degree, partial Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Panel Thickness For Which Designed: 0.062 inches Features Provided: Blackout degree, partial Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Panel Thickness For Which Designed:  0.062 inches  Features Provided:  Blackout degree, partial  Lamp Type Accommodated And Quantity:  1 incandescent  Lens Type:  Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
0.062 inches  Features Provided:  Blackout degree, partial  Lamp Type Accommodated And Quantity:  1 incandescent  Lens Type:  Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
Features Provided: Blackout degree, partial  Lamp Type Accommodated And Quantity: 1 incandescent  Lens Type: Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Blackout degree, partial  Lamp Type Accommodated And Quantity:  1 incandescent  Lens Type:  Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
Lamp Type Accommodated And Quantity:  1 incandescent  Lens Type:  Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
1 incandescent  Lens Type:  Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
Lens Type:  Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
Convex, knurled, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
Transparent single light 1st position horizontal
Transmitted Light Color:
Red single light 1st position horizontal full display division a
Lens Back Surface Condition:
Smooth single light 1st position horizontal
Lens Face Surface Condition:
Smooth single light 1st position horizontal
Smooth single light 1st position horizontal  Special Features:
Special Features:
Special Features: With round flange

Nickel body

## NSN 6210-01-212-9587

Indicator Light - Page 2 of 2



Style Designator:
Round frame, round lens type
Furnished Items And Quantity:
1 hexagon nut and 1 lock washer
Terminal Type And Quantity:
2 corow

2 screw

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A065a0