NSN 6210-01-219-7730

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-219-7730

Hazardous Locations/environmental Protection:
Shock proof and watertight
Overall Length:
2.430 inches
Overall Height:
1.750 inches
Overall Width:
2.125 inches
Lamp Base Type Accommodated:
Midget screw
Lamp Bulb Size Designator:
T-1 3/4
Lens Quantity:
1
Lens Color:
Green single light 1st position horizontal
Multilamp Circuit Type:
Two lamp common
Lamp Industry Number:
1769
Lens Mounting Method:
Lens Mounting Method.
Screw on
Screw on
Screw on Mounting Method:
Screw on Mounting Method: Unthreaded hole
Screw on Mounting Method: Unthreaded hole Features Provided:
Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer
Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity:
Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent
Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type:
Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal
Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal Lens Light Transmission Characteristic:
Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal
Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color:
Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: White single light 1st position horizontal full display division a
Screw on Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: White single light 1st position horizontal full display division a Lens Legend:
Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: White single light 1st position horizontal full display division a Lens Legend: Motor; running single light 1st position horizontal full display division a
Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: White single light 1st position horizontal full display division a Lens Legend: Motor; running single light 1st position horizontal full display division a Transmitted Light Color:
Mounting Method: Unthreaded hole Features Provided: Blackout degree, complete and dimming device and transformer Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: White single light 1st position horizontal full display division a Lens Legend: Motor; running single light 1st position horizontal full display division a Transmitted Light Color: Green single light 1st position horizontal full display division a

Smooth single light 1st position horizontal

NSN 6210-01-219-7730

Indicator Light - Page 2 of 2



Special Features:
117v 60 cycles
Material:
Copper alloy body
Style Designator:
Rectangular frame type
Furnished Items And Quantity:
10 flat washer and 1 gasket and 8 screw
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A065a0