NSN 6210-01-222-0516

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-222-0516

| view Offiline at https://aerobasegroup.com/hsh/oz10-01-222-0010 |
|--|
| Hazardous Locations/environmental Protection: |
| Shock resistant and vibration resistant |
| Overall Length: |
| 2.070 inches |
| Overall Height: |
| 0.960 inches |
| Overall Width: |
| 1.200 inches |
| Filter Color: |
| Red single light 1st position horizontal 4way split display division d |
| Lamp Base Type Accommodated: |
| Midget flanged |
| Lamp Bulb Size Designator: |
| T-1 3/4 |
| Lens Quantity: |
| 1 |
| Lens Color: |
| White single light 1st position horizontal |
| Filter Quantity: |
| 4 |
| Multilamp Circuit Type: |
| Four lamp common |
| Lens Mounting Method: |
| Flange |
| Mounting Method: |
| Panel |
| Panel Thickness For Which Designed: |
| Between 0.050 inches and 0.250 inches |
| Panel Accommodation Hole Width: |
| 1.115 inches |
| Lamp Type Accommodated And Quantity: |
| 4 incandescent |
| Lens Type: |
| Display screen single light 1st position horizontal |
| Panel Accommodation Hole Height: |
| 0.875 inches |
| Lens Light Transmission Characteristic: |
| Translucent single light 1st position horizontal |
| Transmitted Light Color: |
| Red single light 1st position horizontal 4way split display division d |
| Lens Back Surface Condition: |

Smooth single light 1st position horizontal

NSN 6210-01-222-0516 Indicator Light - Page 2 of 2



| Lens Face Surface Condition: |
|--|
| Smooth single light 1st position horizonta |
| Style Designator: |
| Rectangular frame type |
| Terminal Type And Quantity: |
| 6 solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A065a0