## NSN 6210-01-223-5713

Indicator Light - Page 1 of 2



## View Online at https://aerobasegroup.com/nsn/6210-01-223-5713 Hazardous Locations/environmental Protection: Dustproof and fungus resistant and humidity resistant and salt spray proof and shock proof **Overall Length:** 1.290 inches **Overall Diameter:** 0.500 inches Lens Quantity: 1 Lens Color: Red single light 1st position horizontal **Panel Accommodation Hole Diameter:** Between 0.382 inches and 0.391 inches **Mounting Method:** Panel Panel Thickness For Which Designed: Between 0.062 inches and 0.125 inches Lamp Type Accommodated And Quantity: 1 light emitting diode Lens Type: Cylindrical, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal **Transmitted Light Color:** Red single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Fresnel single light 1st position horizontal Material: Aluminum alloy 2011 body **Precious Material And Location:** Terminals gold **Precious Material And Weight:** 0.040 gold grains, troy **Precious Material:** Gold Surface Treatment: Anodize body Style Designator: Round frame, round lens type **Furnished Items And Quantity:**

1 knurled flange ring and 1 lock washer

## NSN 6210-01-223-5713

Indicator Light - Page 2 of 2

## Terminal Type And Quantity:

2 solder stud

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A065a0

