NSN 6210-01-223-6051 Light Lens - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/6210-01-223-6051 |
|--|
| Hazardous Locations/environmental Protection: |
| Heat resistant |
| Overall Length: |
| Between 0.660 inches and 0.670 inches |
| Overall Height: |
| Between 0.050 inches and 0.060 inches |
| Overall Width: |
| Between 0.660 inches and 0.670 inches |
| Effective Length: |
| Between 0.629 inches and 0.639 inches |
| Mounting Device Quantity: |
| 1 |
| End Application: |
| Kidd class ddg; ticonderoga class c (47); spruance class dd(963); virginia class cgn(41); nimitz class cvn; oliver perry class ffg; forresta |
| class cv; arleigh burke class ddg; close in weapon system (ciws-phalanx); fms-build frigates class ships; wasp class lhd |
| Flange Width: |
| Between 0.011 inches and 0.021 inches |
| Mounting Method: |
| Flange |
| Features Provided: |
| Reversed inscription method |
| Light Transmission Design: |
| Transparent lens |
| Inscription: |
| Opr back and test back |
| Surface Condition Color: |
| Black back |
| Color: |
| White lens |
| Material: |
| Plastic lens |
| Surface Condition: |
| Smooth face |
| Style Designator: |
| Flat |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A528d0