NSN 6210-01-234-6589

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-234-6589

Hazardous Locations/environmental Protection:					
Humidity resistant					
Overall Diameter:					
0.891 inches					
Lamp Base Type Accommodated:					
Miniature bayonet					
Lamp Bulb Size Designator:					
T-3 1/4					
Lens Quantity:					
1					
Lens Color:					
White single light 1st position horizontal					
Panel Accommodation Hole Diameter:					
0.688 inches					
Lens Mounting Method:					
Screw on					
Mounting Method:					
Panel					
Panel Thickness For Which Designed:					
0.312 inches					
Lamp Type Accommodated And Quantity:					
1 neon					
Lens Type:					
Dome, knurled, internal thread single light 1st position horizontal					
Lens Light Transmission Characteristic:					
Translucent single light 1st position horizontal					
Translucent single light 1st position horizontal Transmitted Light Color:					
Transmitted Light Color:					
Transmitted Light Color: White single light 1st position horizontal full display division a					
Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition:					
Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal					
Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:					
Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal					
Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material:					
Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body					
Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment:					
Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment: Nickel body					
Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment: Nickel body Style Designator:					
Transmitted Light Color: White single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Copper alloy body Surface Treatment: Nickel body Style Designator: Round frame, round lens type					

2 screw

NSN 6210-01-234-6589

Indicator Light - Page 2 of 2



_				
c	hο	JIF.		ife:
J	116		_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0