NSN 6210-01-235-7094

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-235-7094

Hazardous Locations/environmental Protection:
Oiltight and watertight
Overall Length:
2.999 inches
Overall Diameter:
1.203 inches
Lamp Base Type Accommodated:
Double contact bayonet candelabra export
Lamp Bulb Size Designator:
S-6
Lens Quantity:
1
Lens Color:
Amber single light 1st position horizontal
Panel Accommodation Hole Diameter:
1.000 inches
Lens Mounting Method:
Screw on
Mounting Method:
Panel
Panel Thickness For Which Designed:
0.062 inches
Lamp Type Accommodated And Quantity:
Lamp Type Accommodated And Quantity: 1 incandescent
1 incandescent
1 incandescent Lens Type:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a Lens Back Surface Condition:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Concentric rings single light 1st position horizontal Material:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Concentric rings single light 1st position horizontal
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Concentric rings single light 1st position horizontal Material: Copper alloy body Surface Treatment:
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Concentric rings single light 1st position horizontal Material: Copper alloy body Surface Treatment: Chromium body
1 incandescent Lens Type: Dome, knurled, internal thread single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Amber single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Concentric rings single light 1st position horizontal Material: Copper alloy body Surface Treatment:

1 hexagon nut and 1 lock washer

NSN 6210-01-235-7094

Indicator Light - Page 2 of 2



Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A065a0