NSN 6210-01-256-9038

Indicator Light Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-256-9038

Hazardous Locations/environmental Protection:
Shock proof and watertight
Overall Height:
3.840 inches
Overall Width:
3.750 inches
Lamp Base Type Accommodated:
Midget screw
Lamp Bulb Size Designator:
T-1 3/4
Lens Quantity:
2
Lens Color:
White single row 2nd position vertical
Lamp Industry Number:
1769
Mounting Method:
Bolt
Features Provided:
Transformer
Lamp Type Accommodated And Quantity:
• • • •
4 incandescent
4 incandescent
4 incandescent Lens Type:
4 incandescent Lens Type: Flat, round single row 2nd position vertical
4 incandescent Lens Type: Flat, round single row 2nd position vertical Lens Light Transmission Characteristic:
4 incandescent Lens Type: Flat, round single row 2nd position vertical Lens Light Transmission Characteristic: Translucent single row 2nd position vertical
4 incandescent Lens Type: Flat, round single row 2nd position vertical Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color:
4 incandescent Lens Type: Flat, round single row 2nd position vertical Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: Black single row 1st position vertical full display division a
4 incandescent Lens Type: Flat, round single row 2nd position vertical Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: Black single row 1st position vertical full display division a Lens Legend:
4 incandescent Lens Type: Flat, round single row 2nd position vertical Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: Black single row 1st position vertical full display division a Lens Legend: Car at; main dk single row 2nd position vertical full display division a
4 incandescent Lens Type: Flat, round single row 2nd position vertical Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: Black single row 1st position vertical full display division a Lens Legend: Car at; main dk single row 2nd position vertical full display division a Transmitted Light Color:
4 incandescent Lens Type: Flat, round single row 2nd position vertical Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: Black single row 1st position vertical full display division a Lens Legend: Car at; main dk single row 2nd position vertical full display division a Transmitted Light Color: White single row 2nd position vertical full display division a
4 incandescent Lens Type: Flat, round single row 2nd position vertical Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: Black single row 1st position vertical full display division a Lens Legend: Car at; main dk single row 2nd position vertical full display division a Transmitted Light Color: White single row 2nd position vertical full display division a Lens Back Surface Condition:
4 incandescent Lens Type: Flat, round single row 2nd position vertical Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: Black single row 1st position vertical full display division a Lens Legend: Car at; main dk single row 2nd position vertical full display division a Transmitted Light Color: White single row 2nd position vertical full display division a Lens Back Surface Condition: Smooth single row 2nd position vertical
4 incandescent Lens Type: Flat, round single row 2nd position vertical Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: Black single row 1st position vertical full display division a Lens Legend: Car at; main dk single row 2nd position vertical full display division a Transmitted Light Color: White single row 2nd position vertical full display division a Lens Back Surface Condition: Smooth single row 2nd position vertical Lens Face Surface Condition:
4 incandescent Lens Type: Flat, round single row 2nd position vertical Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: Black single row 1st position vertical full display division a Lens Legend: Car at; main dk single row 2nd position vertical full display division a Transmitted Light Color: White single row 2nd position vertical full display division a Lens Back Surface Condition: Smooth single row 2nd position vertical Lens Face Surface Condition: Smooth single row 2nd position vertical
4 incandescent Lens Type: Flat, round single row 2nd position vertical Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: Black single row 1st position vertical full display division a Lens Legend: Car at; main dk single row 2nd position vertical full display division a Transmitted Light Color: White single row 2nd position vertical full display division a Lens Back Surface Condition: Smooth single row 2nd position vertical Lens Face Surface Condition: Smooth single row 2nd position vertical Material:
4 incandescent Lens Type: Flat, round single row 2nd position vertical Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: Black single row 1st position vertical full display division a Lens Legend: Car at; main dk single row 2nd position vertical full display division a Transmitted Light Color: White single row 2nd position vertical full display division a Lens Back Surface Condition: Smooth single row 2nd position vertical Lens Face Surface Condition: Smooth single row 2nd position vertical Material: Plastic body

4 solder lug

NSN 6210-01-256-9038

Indicator Light Assembly - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0