NSN 6210-01-263-9310

Hazardous Locations/environmental Protection:

Indicator Light - Page 1 of 2

Shock resistant and vibration resistant



View Online at https://aerobasegroup.com/nsn/6210-01-263-9310

Overall Length:
2.040 inches
Overall Height:
0.960 inches
Overall Width:
1.200 inches
Filter Color:
Amber single light 1st position horizontal full display division a
Lamp Base Type Accommodated:
Midget flanged
Lamp Bulb Size Designator:
T-1 3/4
Lens Quantity:
1
Lens Color:
Colorless single light 1st position horizontal
Filter Quantity:
4
Multilamp Circuit Type:
Horizontal split
Lens Mounting Method:
Lens Mounting Method: Flange
Flange
Flange Mounting Method:
Flange Mounting Method: Panel
Flange Mounting Method: Panel Panel Thickness For Which Designed:
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.050 inches and 0.250 inches
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.050 inches and 0.250 inches Panel Accommodation Hole Width:
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.050 inches and 0.250 inches Panel Accommodation Hole Width: 1.115 inches
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.050 inches and 0.250 inches Panel Accommodation Hole Width: 1.115 inches Lamp Type Accommodated And Quantity:
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.050 inches and 0.250 inches Panel Accommodation Hole Width: 1.115 inches Lamp Type Accommodated And Quantity: 4 incandescent
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.050 inches and 0.250 inches Panel Accommodation Hole Width: 1.115 inches Lamp Type Accommodated And Quantity: 4 incandescent Lens Type:
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.050 inches and 0.250 inches Panel Accommodation Hole Width: 1.115 inches Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, rectangular single light 1st position horizontal
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.050 inches and 0.250 inches Panel Accommodation Hole Width: 1.115 inches Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, rectangular single light 1st position horizontal Panel Accommodation Hole Height:
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.050 inches and 0.250 inches Panel Accommodation Hole Width: 1.115 inches Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, rectangular single light 1st position horizontal Panel Accommodation Hole Height: 0.875 inches
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.050 inches and 0.250 inches Panel Accommodation Hole Width: 1.115 inches Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, rectangular single light 1st position horizontal Panel Accommodation Hole Height: 0.875 inches Lens Light Transmission Characteristic:
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.050 inches and 0.250 inches Panel Accommodation Hole Width: 1.115 inches Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, rectangular single light 1st position horizontal Panel Accommodation Hole Height: 0.875 inches Lens Light Transmission Characteristic: Transparent single light 1st position horizontal
Flange Mounting Method: Panel Panel Thickness For Which Designed: Between 0.050 inches and 0.250 inches Panel Accommodation Hole Width: 1.115 inches Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, rectangular single light 1st position horizontal Panel Accommodation Hole Height: 0.875 inches Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color:

NSN 6210-01-263-9310

Indicator Light - Page 2 of 2



Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Plastic body Style Designator: Rectangular frame type Terminal Type And Quantity: 5 solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization:

No Fiig: A065a0