NSN 6210-01-283-5361

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-283-5361

| Hazardous Locations/environmental Protection: |
|---|
| Moisture resistant and shock resistant |
| Overall Length: |
| 3.060 inches |
| Overall Height: |
| 0.740 inches |
| Overall Width: |
| 0.740 inches |
| Filter Color: |
| Red single light 1st position horizontal horizontal split display division b |
| Lamp Base Type Accommodated: |
| Midget flanged |
| Lamp Bulb Size Designator: |
| T-1 3/4 |
| Lens Quantity: |
| 1 |
| Lens Color: |
| White single light 1st position horizontal |
| Filter Quantity: |
| 2 |
| Lamp Industry Number: |
| |
| 327 |
| 327 Lens Mounting Method: |
| |
| Lens Mounting Method: |
| Lens Mounting Method: Flange |
| Lens Mounting Method: Flange Mounting Method: |
| Lens Mounting Method: Flange Mounting Method: Rack |
| Lens Mounting Method: Flange Mounting Method: Rack Lamp Type Accommodated And Quantity: |
| Lens Mounting Method: Flange Mounting Method: Rack Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: |
| Lens Mounting Method: Flange Mounting Method: Rack Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Display screen single light 1st position horizontal |
| Lens Mounting Method: Flange Mounting Method: Rack Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Display screen single light 1st position horizontal Lens Light Transmission Characteristic: |
| Lens Mounting Method: Flange Mounting Method: Rack Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Display screen single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal |
| Lens Mounting Method: Flange Mounting Method: Rack Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Display screen single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: |
| Lens Mounting Method: Flange Mounting Method: Rack Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Display screen single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal |
| Lens Mounting Method: Flange Mounting Method: Rack Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Display screen single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal split display division b Lens Back Surface Condition: |
| Lens Mounting Method: Flange Mounting Method: Rack Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Display screen single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal split display division b |
| Lens Mounting Method: Flange Mounting Method: Rack Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Display screen single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal split display division b Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: |
| Lens Mounting Method: Flange Mounting Method: Rack Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Display screen single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal split display division b Lens Back Surface Condition: Smooth single light 1st position horizontal |
| Lens Mounting Method: Flange Mounting Method: Rack Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Display screen single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Light Color: Red single light 1st position horizontal split display division b Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal |

Rectangular frame type

NSN 6210-01-283-5361

Indicator Light - Page 2 of 2



| Terminal | Type | And | Quantity: |
|-----------------|-------------|-----|-----------|
|-----------------|-------------|-----|-----------|

5 solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0