NSN 6210-01-283-7852

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-283-7852

Hazardous Locations/environmental Protection:

Dust resistant and electromagnetic radiation suppressive and fungus resistant and humidity resistant and moisture resistant and salt spray

resistant and shock resistant and vibration resistant and explosion proof and sand resistant

Overall Length: 2.360 inches **Overall Height:** 0.750 inches **Overall Width:** 0.750 inches Lamp Base Type Accommodated: Submidget flanged Lamp Bulb Size Designator: T-1 Lens Quantity: 1 Lens Color: Red single light 1st position horizontal Multilamp Circuit Type: Four lamp common Lens Mounting Method: Push in **Mounting Method:** Panel Panel Thickness For Which Designed: Between 0.032 inches and 0.187 inches Panel Accommodation Hole Width: Between 0.689 inches and 0.699 inches Lamp Type Accommodated And Quantity: 4 incandescent Lens Type: Flat, square shank single light 1st position horizontal **Panel Accommodation Hole Height:** Between 0.689 inches and 0.699 inches Lens Light Transmission Characteristic: Translucent single light 1st position horizontal **Transmitted Legend Color:** Red single light 1st position horizontal horizontal split display division b Lens Legend: Lru 2 single light 1st position horizontal horizontal split display division b **Transmitted Light Color:** Black single light 1st position horizontal horizontal split display division b Lens Back Surface Condition:

Painted single light 1st position horizontal

NSN 6210-01-283-7852

Indicator Light - Page 2 of 2



Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Stainless steel body **Precious Material And Location:** Terminals gold **Precious Material And Weight:** 0.040 gold grains, troy **Precious Material:** Gold Style Designator: Rectangular frame type **Furnished Items And Quantity:** 1 mounting sleeve **Terminal Type And Quantity:** 5 solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A065a0