

View Online at <https://aerobasegroup.com/nsn/6210-01-283-7853>

Hazardous Locations/environmental Protection:

Dust resistant and electromagnetic radiation suppressive and fungus resistant and humidity resistant and moisture resistant and salt spray resistant and shock resistant and vibration resistant and explosion proof and sand resistant

Overall Length:

2.360 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

Lamp Base Type Accommodated:

Submidget flanged

Lamp Bulb Size Designator:

T-1

Lens Quantity:

1

Lens Color:

Yellow single light 1st position horizontal

Multilamp Circuit Type:

Four lamp common

Lens Mounting Method:

Push in

Mounting Method:

Panel

Panel Thickness For Which Designed:

Between 0.032 inches and 0.187 inches

Panel Accommodation Hole Width:

Between 0.689 inches and 0.699 inches

Lamp Type Accommodated And Quantity:

4 incandescent

Lens Type:

Flat, square shank single light 1st position horizontal

Panel Accommodation Hole Height:

Between 0.689 inches and 0.699 inches

Lens Light Transmission Characteristic:

Translucent single light 1st position horizontal

Transmitted Legend Color:

Yellow single light 1st position horizontal horizontal split display division b

Lens Legend:

Lru 2 single light 1st position horizontal horizontal split display division b

Transmitted Light Color:

Black single light 1st position horizontal horizontal split display division b

Lens Back Surface Condition:

Painted single light 1st position horizontal

Lens Face Surface Condition:

Smooth single light 1st position horizontal

Material:

Stainless steel body

Precious Material And Location:

Terminals gold

Precious Material And Weight:

0.040 gold grains, troy

Precious Material:

Gold

Style Designator:

Rectangular frame type

Furnished Items And Quantity:

1 mounting sleeve

Terminal Type And Quantity:

5 solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0