NSN 6210-01-283-7853

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-283-7853

Hazardous Locations/environmental Protection:
Dust resistant and electromagnetic radiation suppressive and fungus resistant and humidity resistant and moisture resistant and salt spray
resistant and shock resistant and vibration resistant and explosion proof and sand resistant
Overall Length:
2.360 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Lamp Base Type Accommodated:
Submidget flanged
Lamp Bulb Size Designator:
T-1
Lens Quantity:
1
Lens Color:

Yellow single light 1st position horizontal

Multilamp Circuit Type:

Four lamp common

Lens Mounting Method:

Push in

Mounting Method:

Panel

Panel Thickness For Which Designed:

Between 0.032 inches and 0.187 inches

Panel Accommodation Hole Width:

Between 0.689 inches and 0.699 inches

Lamp Type Accommodated And Quantity:

4 incandescent

Lens Type:

Flat, square shank single light 1st position horizontal

Panel Accommodation Hole Height:

Between 0.689 inches and 0.699 inches

Lens Light Transmission Characteristic:

Translucent single light 1st position horizontal

Transmitted Legend Color:

Yellow single light 1st position horizontal horizontal split display division b

Lens Legend:

Lru 2 single light 1st position horizontal horizontal split display division b

Transmitted Light Color:

Black single light 1st position horizontal horizontal split display division b

Lens Back Surface Condition:

Painted single light 1st position horizontal

NSN 6210-01-283-7853

Indicator Light - Page 2 of 2



Lens Face Surface Condition:
Smooth single light 1st position horizontal
Material:
Stainless steel body
Precious Material And Location:
Terminals gold
Precious Material And Weight:
0.040 gold grains, troy
Precious Material:
Gold
Style Designator:
Rectangular frame type
Furnished Items And Quantity:
1 mounting sleeve
Terminal Type And Quantity:
5 solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A065a0