

View Online at <https://aerobasegroup.com/nsn/6210-01-287-5418>

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Diameter:

0.500 inches

Lens Quantity:

1

Lens Color:

White single light 1st position horizontal

Panel Accommodation Hole Diameter:

0.375 inches

End Application:

Engine, marine gas turbine, Im-2500

Lens Mounting Method:

Screw on

Mounting Method:

Panel

Panel Thickness For Which Designed:

Between 0.062 inches and 0.312 inches

Lamp Type Accommodated And Quantity:

1 light emitting diode

Lens Type:

Dome, knurled, internal thread single light 1st position horizontal

Lens Light Transmission Characteristic:

Translucent single light 1st position horizontal

Transmitted Light Color:

White single light 1st position horizontal full display division a

Lens Back Surface Condition:

Fresnel single light 1st position horizontal

Lens Face Surface Condition:

Smooth single light 1st position horizontal

Special Features:

Furnished w/yellow light emitting diode

Material:

Aluminum body

Surface Treatment:

Anodize body

Style Designator:

Round frame, round lens type

Furnished Items And Quantity:

1 hexagon nut and 1 lock washer

Terminal Type And Quantity:

2 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0