

View Online at <https://aerobasegroup.com/nsn/6210-01-287-5418>

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Overall Diameter:**

0.500 inches

**Lens Quantity:**

1

**Lens Color:**

White single light 1st position horizontal

**Panel Accommodation Hole Diameter:**

0.375 inches

**End Application:**

Engine, marine gas turbine, Im-2500

**Lens Mounting Method:**

Screw on

**Mounting Method:**

Panel

**Panel Thickness For Which Designed:**

Between 0.062 inches and 0.312 inches

**Lamp Type Accommodated And Quantity:**

1 light emitting diode

**Lens Type:**

Dome, knurled, internal thread single light 1st position horizontal

**Lens Light Transmission Characteristic:**

Translucent single light 1st position horizontal

**Transmitted Light Color:**

White single light 1st position horizontal full display division a

**Lens Back Surface Condition:**

Fresnel single light 1st position horizontal

**Lens Face Surface Condition:**

Smooth single light 1st position horizontal

**Special Features:**

Furnished w/yellow light emitting diode

**Material:**

Aluminum body

**Surface Treatment:**

Anodize body

**Style Designator:**

Round frame, round lens type

**Furnished Items And Quantity:**

1 hexagon nut and 1 lock washer

**Terminal Type And Quantity:**

2 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A065a0