## NSN 6210-01-288-2909

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-288-2909

Hazardous Locations/environmental Protection:
Dripproof
Overall Length:
1.468 inches
Overall Diameter:
0.562 inches
Lamp Base Type Accommodated:
Midget flanged
Lamp Bulb Size Designator:
T-1 3/4
Lens Quantity:
1
Lens Color:
Colorless single light 1st position horizontal
Panel Accommodation Hole Diameter:
0.469 inches
End Application:
Support equipment, b-1 aircraft
Lens Mounting Method:
Screw in
Mounting Method:
Panel
-
Panel
Panel Thickness For Which Designed:
Panel Panel Thickness For Which Designed: 0.312 inches
Panel Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity:
Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type:
Panel Thickness For Which Designed: 0.312 inches  Lamp Type Accommodated And Quantity: 1 incandescent  Lens Type: Flat, threaded shank single light 1st position horizontal
Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic:
Panel Thickness For Which Designed:  0.312 inches  Lamp Type Accommodated And Quantity:  1 incandescent  Lens Type:  Flat, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal
Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color:
Panel Thickness For Which Designed: 0.312 inches  Lamp Type Accommodated And Quantity: 1 incandescent  Lens Type: Flat, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Colorless single light 1st position horizontal full display division a
Panel Thickness For Which Designed:  0.312 inches  Lamp Type Accommodated And Quantity:  1 incandescent  Lens Type:  Flat, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Colorless single light 1st position horizontal full display division a  Lens Back Surface Condition:
Panel Thickness For Which Designed: 0.312 inches  Lamp Type Accommodated And Quantity: 1 incandescent  Lens Type: Flat, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic: Transparent single light 1st position horizontal  Transmitted Light Color: Colorless single light 1st position horizontal full display division a  Lens Back Surface Condition: Smooth single light 1st position horizontal
Panel Thickness For Which Designed: 0.312 inches  Lamp Type Accommodated And Quantity: 1 incandescent  Lens Type: Flat, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Colorless single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:
Panel Thickness For Which Designed: 0.312 inches  Lamp Type Accommodated And Quantity: 1 incandescent  Lens Type: Flat, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic: Transparent single light 1st position horizontal  Transmitted Light Color: Colorless single light 1st position horizontal full display division a  Lens Back Surface Condition: Smooth single light 1st position horizontal
Panel Thickness For Which Designed: 0.312 inches Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Flat, threaded shank single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Colorless single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material:
Panel Thickness For Which Designed:  0.312 inches  Lamp Type Accommodated And Quantity:  1 incandescent  Lens Type:  Flat, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Colorless single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal
Panel Thickness For Which Designed:  0.312 inches  Lamp Type Accommodated And Quantity:  1 incandescent  Lens Type: Flat, threaded shank single light 1st position horizontal  Lens Light Transmission Characteristic:  Transparent single light 1st position horizontal  Transmitted Light Color:  Colorless single light 1st position horizontal full display division a  Lens Back Surface Condition:  Smooth single light 1st position horizontal  Lens Face Surface Condition:  Smooth single light 1st position horizontal  Material:  Aluminum body

Round frame, round lens type

## NSN 6210-01-288-2909

Indicator Light - Page 2 of 2



Furni	ished	<b>Items</b>	And	Quantity	<b>/</b> :

1 gasket and 1 hexagon nut and 1 lock washer

**Terminal Type And Quantity:** 

2 solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A065a0