## NSN 6210-01-339-6017

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-339-6017

### Hazardous Locations/environmental Protection:

Dustproof and explosion proof nec cl.I, gp.Abcd; cl.Ii, gp.Efg; cl.Iii and salt spray resistant and shock resistant and vibration resistant

#### **Overall Length:**

2.320 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

0.750 inches

#### Lamp Base Type Accommodated:

Midget flanged

#### Lamp Bulb Size Designator:

T-1

#### Multilamp Circuit Type:

Four lamp common

#### Mounting Method:

Panel

#### Panel Thickness For Which Designed:

Between 0.032 inches and 0.187 inches

#### Panel Accommodation Hole Width:

Between 0.689 inches and 0.699 inches

#### Lamp Type Accommodated And Quantity:

4 incandescent

#### Panel Accommodation Hole Height:

Between 0.689 inches and 0.699 inches

#### Lens Legend:

Light aff avail single light 1st position horizontal full display division a

#### **Transmitted Light Color:**

Red single light 1st position horizontal full display division a

#### **Precious Material And Location:**

Terminals gold

#### **Precious Material And Weight:**

0.040 gold grains, troy

#### **Precious Material:**

Gold

#### Style Designator:

Rectangular frame type

Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# **NSN 6210-01-339-6017** Indicator Light - Page 2 of 2

Fiig: A065a0

