Lighting Fixture - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/6210-01-343-2421 |
|---|
| Hazardous Locations/environmental Protection: |
| Shock resistant and vibration resistant |
| Overall Length: |
| 18.594 inches |
| Overall Height: |
| 2.500 inches |
| Overall Width: |
| 3.688 inches |
| Lamp Base Type Accommodated: |
| Medium bipin |
| Lens Color: |
| White |
| Lens Transparency: |
| Translucent |
| Illumination Directing Device Type: |
| Window |
| Voltage Rating In Volts: |
| 120.0 ac |
| Mounting Method: |
| Unthreaded hole |
| Lamp Type Accommodated And Quantity: |
| 1 fluorescent |
| Lens Type And Quantity: |
| 1 flat, rectangular, framed |
| Lens Surface Condition: |
| Smooth backsmooth face |
| Material: |
| Plastic acrylic illumination directing device |
| Material Specification: |
| Mil-p-24191, ty wtls-3, grade c military specification single material response illumination directing device |
| Shape: |
| Rectangular |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| Demilitarization: |
| No |
| Fiig: |
| A06300 |
| Mil-std (military Standard): |
| Mil-p-24191 spec. |
| |