## NSN 6210-01-343-8408

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-343-8408

Hazardous Locations/environmental Protection: Radio frequency interference **Overall Length:** Between 1.510 inches and 1.610 inches **Overall Height:** 0.750 inches **Overall Width:** 0.750 inches Lamp Base Type Accommodated: Submidget flanged Lamp Bulb Size Designator: T-1 Lens Quantity: 1 Lens Color: Amber single light 1st position horizontal Multilamp Circuit Type: Four lamp common **End Application:** Milstar system Lens Mounting Method: Push in **Mounting Method:** Panel Panel Thickness For Which Designed: 0.250 inches Panel Accommodation Hole Width: Between 0.689 inches and 0.699 inches Lamp Type Accommodated And Quantity: 4 light emitting diode Lens Type: Flat, square end cap single light 1st position horizontal **Panel Accommodation Hole Height:** Between 0.689 inches and 0.699 inches Lens Light Transmission Characteristic: Transparent single light 1st position horizontal **Transmitted Legend Color:** Amber single light 1st position horizontal full display division a Lens Legend: Call single light 1st position horizontal full display division a **Transmitted Light Color:** 

Amber single light 1st position horizontal full display division a

## NSN 6210-01-343-8408

Indicator Light - Page 2 of 2



Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Material: Plastic lens **Precious Material And Location:** Terminals gold **Precious Material And Weight:** 0.040 gold grains, troy **Precious Material:** Gold Style Designator: Rectangular frame type **Terminal Type And Quantity:** 3 solder stud Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A065a0