## NSN 6210-01-355-4029

Indicator Light Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-355-4029

## **Hazardous Locations/environmental Protection:**

**Lens Face Surface Condition:** 

Smooth single row 3rd position vertical

Electromagnetic radiation suppressive and fungus resistant and humidity resistant and shock resistant and vibration resistant and watertight

Overall Length:
2.093 inches
Overall Height:
1.500 inches
Overall Width:
0.688 inches
Filter Color:
Green single row 1st position vertical full display division a
Lamp Base Type Accommodated:
Midget flanged
Lamp Bulb Size Designator:
T-1 3/4
Lens Quantity:
3
Lens Color:
Colorless single row 3rd position vertical
Filter Quantity:
3
Lamp Industry Number:
387
Lens Mounting Method:
Push in
Mounting Method:
Panel
Lamp Type Accommodated And Quantity:
6 incandescent
Lens Type:
Flat, rectangular single row 1st position vertical
Lens Light Transmission Characteristic:
Translucent single row 3rd position vertical
Transmitted Legend Color:
Black single row 3rd position vertical full display division a
Lens Legend:
Stol single row 3rd position vertical full display division a
Transmitted Light Color:
Green single row 1st position vertical full display division a
Lens Back Surface Condition:
Smooth single row 3rd position vertical

## NSN 6210-01-355-4029

Indicator Light Assembly - Page 2 of 2



Special Features
------------------

Between panel thickness for which designed: 0.032 in.; panel accommodation hole width: 0.704 in. And 0.714 in.; panel accommodation hole height: 1.335 in.

Style Designator:

Single strip type

**Terminal Type And Quantity:** 

3 solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A065a0