NSN 6210-01-370-1894

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-370-1894

| Hazardous Locations/environmental Protection: |
|---|
| Dusttight and oiltight |
| Overall Length: |
| 3.108 inches |
| Overall Height: |
| 1.625 inches |
| Overall Width: |
| 2.125 inches |
| Lamp Base Type Accommodated: |
| Wedge |
| Lamp Bulb Size Designator: |
| T-1 3/4 |
| Lens Quantity: |
| 1 |
| Lens Color: |
| Green single light 1st position horizontal |
| Panel Accommodation Hole Diameter: |
| 0.875 inches |
| End Application: |
| Usns stalwart class tagos |
| Lens Mounting Method: |
| Screw on |
| Screw on |
| Mounting Method: |
| |
| Mounting Method: |
| Mounting Method: Panel |
| Mounting Method: Panel Panel Thickness For Which Designed: |
| Mounting Method: Panel Panel Thickness For Which Designed: Between 0.060 inches and 0.250 inches |
| Mounting Method: Panel Panel Thickness For Which Designed: Between 0.060 inches and 0.250 inches Features Provided: |
| Mounting Method: Panel Panel Thickness For Which Designed: Between 0.060 inches and 0.250 inches Features Provided: Transformer |
| Mounting Method: Panel Panel Thickness For Which Designed: Between 0.060 inches and 0.250 inches Features Provided: Transformer Lamp Type Accommodated And Quantity: |
| Mounting Method: Panel Panel Thickness For Which Designed: Between 0.060 inches and 0.250 inches Features Provided: Transformer Lamp Type Accommodated And Quantity: 1 incandescent |
| Mounting Method: Panel Panel Thickness For Which Designed: Between 0.060 inches and 0.250 inches Features Provided: Transformer Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: |
| Mounting Method: Panel Panel Thickness For Which Designed: Between 0.060 inches and 0.250 inches Features Provided: Transformer Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled single light 1st position horizontal |
| Mounting Method: Panel Panel Thickness For Which Designed: Between 0.060 inches and 0.250 inches Features Provided: Transformer Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic: |
| Mounting Method: Panel Panel Thickness For Which Designed: Between 0.060 inches and 0.250 inches Features Provided: Transformer Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal |
| Mounting Method: Panel Panel Thickness For Which Designed: Between 0.060 inches and 0.250 inches Features Provided: Transformer Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: |
| Mounting Method: Panel Panel Thickness For Which Designed: Between 0.060 inches and 0.250 inches Features Provided: Transformer Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Green single light 1st position horizontal full display division a |
| Mounting Method: Panel Panel Thickness For Which Designed: Between 0.060 inches and 0.250 inches Features Provided: Transformer Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Green single light 1st position horizontal full display division a Lens Back Surface Condition: |
| Mounting Method: Panel Panel Thickness For Which Designed: Between 0.060 inches and 0.250 inches Features Provided: Transformer Lamp Type Accommodated And Quantity: 1 incandescent Lens Type: Convex, knurled single light 1st position horizontal Lens Light Transmission Characteristic: Transparent single light 1st position horizontal Transmitted Light Color: Green single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal |

120v 60hz

NSN 6210-01-370-1894

Indicator Light - Page 2 of 2



| Material: |
|-----------------------------|
| Copper alloy body |
| Style Designator: |
| Rectangular frame type |
| Terminal Type And Quantity: |
| 2 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A065a0