NSN 6210-01-373-7019

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-373-7019

Hazardous Locations/environmental Protection:

Vibration resistant and heat resistant and radio frequency interference and shock resistant and vibration resistant
Overall Length:
1.560 inches
Overall Width:
0.240 inches
Filter Color:
Red single light 1st position horizontal horizontal split display division b
Lamp Base Type Accommodated:
Midget flanged
Lamp Bulb Size Designator:
T-1
Lens Quantity:
1
Lens Color:
White single light 1st position horizontal
Filter Quantity:
1
Multilamp Circuit Type:
Four lamp common
Lens Mounting Method:
Flange
Mounting Method:
Panel
Panel Thickness For Which Designed:
Between 0.030 inches and 0.250 inches

Panel Accommodation Hole Width:

Between 0.685 inches and 0.695 inches

Lamp Type Accommodated And Quantity:

4 incandescent

Lens Type:

Flat, rectangular single light 1st position horizontal

Panel Accommodation Hole Height:

Between 0.685 inches and 0.695 inches

Lens Light Transmission Characteristic:

Translucent single light 1st position horizontal

Transmitted Legend Color:

Black single light 1st position horizontal horizontal split display division b

Lens Legend:

Phase loss single light 1st position horizontal horizontal split display division b

Transmitted Light Color:

Red single light 1st position horizontal horizontal split display division b

NSN 6210-01-373-7019

Indicator Light - Page 2 of 2



Lens Back Surface Condition:
Smooth single light 1st position horizontal
Lens Face Surface Condition:
Smooth single light 1st position horizontal
Extra Long Reference Number:
58124a0b15c1 f4 l2 n2 (rr) 17 250v, dc/phase, loss
Material:
Aluminum alloy 5052 body
Style Designator:
Rectangular frame type
Terminal Type And Quantity:
5 solder stud
Reference Number Differentiating Characteristics:
As differentiated by extra long reference number
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A065a0