

View Online at <https://aerobasegroup.com/nsn/6210-01-374-9858>

**Hazardous Locations/environmental Protection:**

Cold resistant and heat resistant and radio frequency interference and shock resistant and vibration resistant

**Overall Length:**

1.560 inches

**Overall Width:**

0.740 inches

**Filter Color:**

Green single light 1st position horizontal horizontal split display division a

**Lamp Base Type Accommodated:**

Midget flanged

**Lamp Bulb Size Designator:**

T-1

**Lens Quantity:**

1

**Lens Color:**

White single light 1st position horizontal

**Filter Quantity:**

1

**Multilamp Circuit Type:**

Four lamp common

**Lens Mounting Method:**

Flange

**Mounting Method:**

Panel

**Panel Thickness For Which Designed:**

Between 0.030 inches and 0.250 inches

**Panel Accommodation Hole Width:**

Between 0.685 inches and 0.695 inches

**Lamp Type Accommodated And Quantity:**

4 incandescent

**Lens Type:**

Flat, rectangular single light 1st position horizontal

**Panel Accommodation Hole Height:**

Between 0.685 inches and 0.695 inches

**Lens Light Transmission Characteristic:**

Translucent single light 1st position horizontal

**Transmitted Legend Color:**

Black single light 1st position horizontal horizontal split display division b

**Lens Legend:**

Remote single light 1st position horizontal horizontal split display division b

**Transmitted Light Color:**

Green single light 1st position horizontal horizontal split display division b

**Lens Back Surface Condition:**

Smooth single light 1st position horizontal

**Lens Face Surface Condition:**

Smooth single light 1st position horizontal

**Extra Long Reference Number:**

58124a0b15c1 f4 l2 n2 (gg) 16 manual/remote

**Material:**

Aluminum alloy 5052 body

**Style Designator:**

Rectangular frame type

**Terminal Type And Quantity:**

5 solder stud

**Reference Number Differentiating Characteristics:**

As differentiated by extra long reference number

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A065a0