Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-420-0352

Hazardous Locations/environmental Protection:

Dripproof

Overall Length:

2.781 inches

Overall Diameter:

0.810 inches

Lamp Base Type Accommodated:

Miniature bayonet

Lamp Bulb Size Designator:

T-3 1/4

Lens Quantity:

1

Lens Color:

Red single light 1st position horizontal

End Application:

Oliver perry class ffg; nimitz class cvn; ticonderoga class cg (47); tarawa class lha; wasp class lhd; spruance class dd (963); forrestal class cv; supply class aoe; whidbey island class lsd; powhatan class t-atf 166; fms build frigates class ships; arleigh burke class ddg

Lens Mounting Method:

Screw in

Mounting Method:

Panel

Lamp Type Accommodated And Quantity:

1 neon

Lens Type:

Stovepipe, knurled single light 1st position horizontal

Lens Light Transmission Characteristic:

Transparent single light 1st position horizontal

Transmitted Light Color:

Red single light 1st position horizontal full display division a

Special Features:

E/i application chassis assembly am-221on/wtc, cage 12763; panel hole diameter 0.691 inches; panel hole width 0.660 inches

Material:

Plastic lens

Style Designator:

Round frame, round lens type

Terminal Type And Quantity:

2 solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 6210-01-420-0352

Indicator Light - Page 2 of 2

Fiig: A065a0

Mil-std (military Standard):

Mil-I-3661 spec.

