NSN 6210-01-460-4962 Lighting Fixture - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/6210-01-460-4962 |
|---|
| Hazardous Locations/environmental Protection: |
| Watertight and shock resistant and vibration proof |
| Overall Length: |
| Between 28.891 inches and 28.953 inches |
| Overall Height: |
| 3.812 inches |
| Overall Width: |
| Between 4.609 inches and 4.656 inches |
| Filter Color: |
| Red |
| Lamp Base Type Accommodated: |
| Medium bipin |
| Wiring Provision Method: |
| Cable |
| Illumination Directing Device Type: |
| Window |
| Wiring Provision Length: |
| 240.0 inches single provision |
| Voltage Rating In Volts: |
| 120.0 ac |
| Mounting Method: |
| Unthreaded hole |
| Lamp Type Accommodated And Quantity: |
| 1 fluorescent |
| Special Features: |
| Has high efficiency lamp and ballast; filter is a tube |
| Material: |
| Plastic acrylic illumination directing device |
| Material Specification: |
| Mil-p-24191, type wtls-4, grade g military specification single material response illumination directing device |
| Surface Treatment: |
| Any acceptable body |
| Shape: |
| Rectangular |
| Furnished Items And Quantity: |
| 1 lamp |
| Terminal Type And Quantity: |
| 1 wire lead |
| Shelf Life: |
| N/a |
| Unit Of Massura: |

NSN 6210-01-460-4962

Lighting Fixture - Page 2 of 2



| | izati | |
|--|-------|--|
| | | |
| | | |

No

Fiig:

A06300

Mil-std (military Standard):

Mil-p-24191 spec.