NSN 6210-01-461-9646

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-461-9646

Hazardous Locations/environmental Protection:				
Shock proof and watertight				
Overall Height:				
3.840 inches				
Overall Width:				
3.750 inches				
Lamp Base Type Accommodated:				
Midget screw				
Lamp Bulb Size Designator:				
T-1 3/4				
Lens Quantity:				
2				
Lens Color:				
Red single row 2nd position vertical				
Lamp Industry Number:				
1769				
Mounting Method:				
Bolt				
Features Provided:				
Transformer				
Lamp Type Accommodated And Quantity:				
4 incandescent				
Lens Type:				
Flat, round single row 2nd position vertical				
Flat, round single row 2nd position vertical Lens Light Transmission Characteristic:				
Lens Light Transmission Characteristic:				
Lens Light Transmission Characteristic: Translucent single row 2nd position vertical				
Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color:				
Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: White single row 2nd position vertical full display division a				
Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: White single row 2nd position vertical full display division a Lens Legend:				
Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: White single row 2nd position vertical full display division a Lens Legend: Slack cable single row 2nd position vertical full display division a				
Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: White single row 2nd position vertical full display division a Lens Legend: Slack cable single row 2nd position vertical full display division a Transmitted Light Color:				
Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: White single row 2nd position vertical full display division a Lens Legend: Slack cable single row 2nd position vertical full display division a Transmitted Light Color: Red single row 2nd position vertical full display division a				
Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: White single row 2nd position vertical full display division a Lens Legend: Slack cable single row 2nd position vertical full display division a Transmitted Light Color: Red single row 2nd position vertical full display division a Lens Back Surface Condition:				
Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: White single row 2nd position vertical full display division a Lens Legend: Slack cable single row 2nd position vertical full display division a Transmitted Light Color: Red single row 2nd position vertical full display division a Lens Back Surface Condition: Smooth single row 2nd position vertical				
Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: White single row 2nd position vertical full display division a Lens Legend: Slack cable single row 2nd position vertical full display division a Transmitted Light Color: Red single row 2nd position vertical full display division a Lens Back Surface Condition: Smooth single row 2nd position vertical Lens Face Surface Condition:				
Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: White single row 2nd position vertical full display division a Lens Legend: Slack cable single row 2nd position vertical full display division a Transmitted Light Color: Red single row 2nd position vertical full display division a Lens Back Surface Condition: Smooth single row 2nd position vertical Lens Face Surface Condition: Smooth single row 2nd position vertical				
Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: White single row 2nd position vertical full display division a Lens Legend: Slack cable single row 2nd position vertical full display division a Transmitted Light Color: Red single row 2nd position vertical full display division a Lens Back Surface Condition: Smooth single row 2nd position vertical Lens Face Surface Condition: Smooth single row 2nd position vertical Special Features:				
Lens Light Transmission Characteristic: Translucent single row 2nd position vertical Transmitted Legend Color: White single row 2nd position vertical full display division a Lens Legend: Slack cable single row 2nd position vertical full display division a Transmitted Light Color: Red single row 2nd position vertical full display division a Lens Back Surface Condition: Smooth single row 2nd position vertical Lens Face Surface Condition: Smooth single row 2nd position vertical Special Features: 115 volt				

Single strip type

NSN 6210-01-461-9646

Indicator Light - Page 2 of 2



Terminal Type And Quantity:	Terminal	Type	And	Quantity:
-----------------------------	----------	------	-----	-----------

4 solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0