NSN 6210-01-474-5959

Indicator Light - Page 1 of 2

Rectangular frame type



View Online at https://aerobasegroup.com/nsn/6210-01-474-5959

Hazardous Locations/environmental Protection:
Shock proof and waterproof
Overall Length:
2.630 inches
Overall Height:
1.750 inches
Overall Width:
2.125 inches
Lamp Base Type Accommodated:
Midget screw
Lamp Bulb Size Designator:
T-1 3/4
Lens Quantity:
1
Lens Color:
White single row 1st position horizontal
Multilamp Circuit Type:
Two lamp common
Lamp Industry Number:
1769
Mounting Method:
Unthreaded hole
Lamp Type Accommodated And Quantity:
Lamp Type Accommodated And Quantity: 2 incandescent
2 incandescent
2 incandescent Lens Type:
2 incandescent Lens Type: Flat, rectangular single row 1st position horizontal
2 incandescent Lens Type: Flat, rectangular single row 1st position horizontal Lens Light Transmission Characteristic:
2 incandescent Lens Type: Flat, rectangular single row 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal
2 incandescent Lens Type: Flat, rectangular single row 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color:
2 incandescent Lens Type: Flat, rectangular single row 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: Black single light 1st position horizontal full display division a
2 incandescent Lens Type: Flat, rectangular single row 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: Black single light 1st position horizontal full display division a Lens Legend:
2 incandescent Lens Type: Flat, rectangular single row 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: Black single light 1st position horizontal full display division a Lens Legend: Stow/hatch sequence single light 1st position horizontal full display division a
2 incandescent Lens Type: Flat, rectangular single row 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: Black single light 1st position horizontal full display division a Lens Legend: Stow/hatch sequence single light 1st position horizontal full display division a Lens Back Surface Condition:
2 incandescent Lens Type: Flat, rectangular single row 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: Black single light 1st position horizontal full display division a Lens Legend: Stow/hatch sequence single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal
2 incandescent Lens Type: Flat, rectangular single row 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: Black single light 1st position horizontal full display division a Lens Legend: Stow/hatch sequence single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:
2 incandescent Lens Type: Flat, rectangular single row 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: Black single light 1st position horizontal full display division a Lens Legend: Stow/hatch sequence single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal
2 incandescent Lens Type: Flat, rectangular single row 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: Black single light 1st position horizontal full display division a Lens Legend: Stow/hatch sequence single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features:
2 incandescent Lens Type: Flat, rectangular single row 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Transmitted Legend Color: Black single light 1st position horizontal full display division a Lens Legend: Stow/hatch sequence single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Special Features: 117 volt, 60 hz; includes 8 screws

NSN 6210-01-474-5959

Indicator Light - Page 2 of 2



F	urnished	Items	And	Quantity	1

10 flat washer and 1 gasket

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A065a0