NSN 6210-01-531-3667

Indicator Light - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6210-01-531-3667

Hazardous Locations/environmental Protection:
Watertight and shock proof
Overall Length:
2.630 inches
Overall Height:
1.750 inches
Overall Width:
2.120 inches
Lamp Base Type Accommodated:
Midget screw
Lens Quantity:
1
Lens Color:
White single light 1st position horizontal
Multilamp Circuit Type:
Two lamp common
Lamp Industry Number:
1717
End Application:
Controller
Lens Mounting Method:
Lens wounting wethou.
Push in
_
Push in
Push in Mounting Method:
Push in Mounting Method: Unthreaded hole
Push in Mounting Method: Unthreaded hole Lamp Type Accommodated And Quantity:
Push in Mounting Method: Unthreaded hole Lamp Type Accommodated And Quantity: 2 incandescent
Push in Mounting Method: Unthreaded hole Lamp Type Accommodated And Quantity: 2 incandescent Lens Type:
Push in Mounting Method: Unthreaded hole Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, rectangular single light 1st position horizontal
Push in Mounting Method: Unthreaded hole Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, rectangular single light 1st position horizontal Lens Light Transmission Characteristic:
Push in Mounting Method: Unthreaded hole Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, rectangular single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal
Push in Mounting Method: Unthreaded hole Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, rectangular single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Legend:
Push in Mounting Method: Unthreaded hole Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, rectangular single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Legend: Port single light 1st position horizontal full display division a
Push in Mounting Method: Unthreaded hole Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, rectangular single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Legend: Port single light 1st position horizontal full display division a Lens Back Surface Condition:
Push in Mounting Method: Unthreaded hole Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, rectangular single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Legend: Port single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal
Push in Mounting Method: Unthreaded hole Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, rectangular single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Legend: Port single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition:
Push in Mounting Method: Unthreaded hole Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, rectangular single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Legend: Port single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal
Push in Mounting Method: Unthreaded hole Lamp Type Accommodated And Quantity: 2 incandescent Lens Type: Flat, rectangular single light 1st position horizontal Lens Light Transmission Characteristic: Translucent single light 1st position horizontal Lens Legend: Port single light 1st position horizontal full display division a Lens Back Surface Condition: Smooth single light 1st position horizontal Lens Face Surface Condition: Smooth single light 1st position horizontal Product Name:

Material:

Plastic polycarbonate lens

NSN 6210-01-531-3667

Indicator Light - Page 2 of 2



nator:

Rectangular frame type

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A065a0