

View Online at <https://aerobasegroup.com/nsn/6220-00-678-9046>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

7.312 inches

Overall Diameter:

5.531 inches

Lamp Base Type Accommodated:

Two contact lugs

Wiring Provision Method:

Individual wire

Illumination Directing Device Type:

Combat hood

End Application:

Truck, f (m10a); helicopter, search and rescue, hh-60h; aircraft, t-39; crane (rt41aa); armored security vehicle, model xm1117; truck, fl(m4k); chassis, truck (tss); shipboard material handling equipment (mhe); truck, tractor (m911 & m746)(het) ; helicopter, uscg search and rescue, hh-60j; helicopter, advance attack, ah-1w; helicopter, mh-53e; helicopter, carrier based asw, sh-60f; nimitz class cvn; forrestal class cv; wasp class lhd

Wiring Provision Length:

Any acceptable all provisions

Voltage Rating In Volts:

24.0 dc

Mounting Method:

Bolt

Features Provided:

Blackout degree, partial

Lamp Type Accommodated And Quantity:

1 incandescent

Special Features:

Headlight position adjustable w/bearing bracket, 30 degrees horizontal adjustment and 5 degrees vertical adjustment, one 0.375 in. -16 unc -2a mtg bolt, 0.812 in. Lg universal mtg

Material:

Steel body

Surface Treatment:

Any acceptable reflector

Shape:

Round

Furnished Items And Quantity:

1 lamp

Terminal Type And Quantity:

1 connector, plug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

A06300