NSN 6220-00-781-0451

Aircraft Cockpit Light - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6220-00-781-0451

Hazardous Locations/environmental Protection: Any acceptable Overall Length: 3.594 inches Overall Diameter: 1.094 inches Lamp Base Type Accommodated: Single contact bayonet candelabra Lens Color: Red, identification, mil-c-25050 type 2 Lens Transparency: Transparent Wiring Provision Method: Individual wire Wiring Provision Length: 4.0 inches second provision Voltage Rating In Volts: 28.0 dc Mounting Method: Unthreaded hole
Overall Length: 3.594 inches Overall Diameter: 1.094 inches Lamp Base Type Accommodated: Single contact bayonet candelabra Lens Color: Red, identification, mil-c-25050 type 2 Lens Transparency: Transparent Wiring Provision Method: Individual wire Wiring Provision Length: 4.0 inches second provision Voltage Rating In Volts: 28.0 dc Mounting Method:
3.594 inches Overall Diameter: 1.094 inches Lamp Base Type Accommodated: Single contact bayonet candelabra Lens Color: Red, identification, mil-c-25050 type 2 Lens Transparency: Transparent Wiring Provision Method: Individual wire Wiring Provision Length: 4.0 inches second provision Voltage Rating In Volts: 28.0 dc Mounting Method:
Overall Diameter: 1.094 inches Lamp Base Type Accommodated: Single contact bayonet candelabra Lens Color: Red, identification, mil-c-25050 type 2 Lens Transparency: Transparent Wiring Provision Method: Individual wire Wiring Provision Length: 4.0 inches second provision Voltage Rating In Volts: 28.0 dc Mounting Method:
1.094 inches Lamp Base Type Accommodated: Single contact bayonet candelabra Lens Color: Red, identification, mil-c-25050 type 2 Lens Transparency: Transparent Wiring Provision Method: Individual wire Wiring Provision Length: 4.0 inches second provision Voltage Rating In Volts: 28.0 dc Mounting Method:
Lamp Base Type Accommodated: Single contact bayonet candelabra Lens Color: Red, identification, mil-c-25050 type 2 Lens Transparency: Transparent Wiring Provision Method: Individual wire Wiring Provision Length: 4.0 inches second provision Voltage Rating In Volts: 28.0 dc Mounting Method:
Single contact bayonet candelabra Lens Color: Red, identification, mil-c-25050 type 2 Lens Transparency: Transparent Wiring Provision Method: Individual wire Wiring Provision Length: 4.0 inches second provision Voltage Rating In Volts: 28.0 dc Mounting Method:
Lens Color: Red, identification, mil-c-25050 type 2 Lens Transparency: Transparent Wiring Provision Method: Individual wire Wiring Provision Length: 4.0 inches second provision Voltage Rating In Volts: 28.0 dc Mounting Method:
Red, identification, mil-c-25050 type 2 Lens Transparency: Transparent Wiring Provision Method: Individual wire Wiring Provision Length: 4.0 inches second provision Voltage Rating In Volts: 28.0 dc Mounting Method:
Lens Transparency: Transparent Wiring Provision Method: Individual wire Wiring Provision Length: 4.0 inches second provision Voltage Rating In Volts: 28.0 dc Mounting Method:
Transparent Wiring Provision Method: Individual wire Wiring Provision Length: 4.0 inches second provision Voltage Rating In Volts: 28.0 dc Mounting Method:
Wiring Provision Method: Individual wire Wiring Provision Length: 4.0 inches second provision Voltage Rating In Volts: 28.0 dc Mounting Method:
Individual wire Wiring Provision Length: 4.0 inches second provision Voltage Rating In Volts: 28.0 dc Mounting Method:
Wiring Provision Length: 4.0 inches second provision Voltage Rating In Volts: 28.0 dc Mounting Method:
4.0 inches second provision Voltage Rating In Volts: 28.0 dc Mounting Method:
Voltage Rating In Volts: 28.0 dc Mounting Method:
28.0 dc Mounting Method:
Mounting Method:
-
Unthreaded hole
Features Provided:
Switch
Lamp Type Accommodated And Quantity:
1 incandescent
Lens Type And Quantity:
1 flat, round
Lens Surface Condition:
Smooth back
Material:
Aluminum body
Furnished Items And Quantity:
1 lamp
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A06300